

# SAFETY DATA SHEET

## SECTION 1 PRODUCT and COMPANY INFORMATION

TRADE NAME: **Castle® North Carolina Yellow Enamel™**

PRODUCT TYPE: Paint  
PRODUCT CODE: C1601-14

MANUFACTURER: Castle Products, Inc  
424 St. Paul Street  
Rochester, NY 14605  
(800) 876-0222  
EMERGENCY (585) 275-3232

## SECTION 2 HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: DANGER: Gases Under Pressure, Flammable, Irritant  
Keep out of reach of children. May be irritating to eyes. May be irritating to skin.

POTENTIAL HEALTH EFFECTS: Eyes: Irritation.  
Skin: Irritation.  
Inhalation: Irritating to mucous membranes.  
Ingestion: Harmful if swallowed. Do not ingest.



## SECTION 3 COMPOSITION INFORMATION ON INGREDIENTS

| INGREDIENTS                | CAS #     | PEL                  | TLV                  | STEL       | %      |
|----------------------------|-----------|----------------------|----------------------|------------|--------|
| Acetone                    | 67-64-1   | 750                  | 750                  | 1000       | 10-20% |
| *Toluene                   | 108-88-3  | 100                  | 100                  | 150        | 20-40% |
| Methyl Ethyl Ketone        | 78-93-3   | 200                  | 200                  | 300        | 10-20% |
| *Xylene                    | 1330-20-7 | 100                  | 100                  | 150        | 20-40% |
| *Chrome Yellow             | 1344-37-2 | .05mg/m <sup>3</sup> | .05mg/m <sup>3</sup> |            | 1-10%  |
| Propane/Isobutane/n-Butane | 74-98-6   | 1000                 | 1000                 | Asphyxiant | 20-30% |
| Non-hazardous              | Mixture   | NE                   | NE                   | NE         | 1-10%  |

\*Acceptable ceiling concentration for Toluene-300ppm; max peak above ceiling-8 hr shift-500 ppm. Technical grade Xylene contains 18-20% Ethylbenzene(CAS# 100-41-4) which has 100ppm PEL, 100ppm TLV, 125 ppm STEL, and is subject to the reporting requirements of Section 313 of SARA Title III. Dried film contains Lead SEIL, and is greater than that allowed for household use. Chrome Yellow contains: Lead(total content)60% of pigment and Chromium(6+)Trioxide 10.5% of pigment.

## SECTION 4 FIRST AID MEASURES

First Aid Procedures:

Eye contact: Hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician if irritation persists.

Skin contact: For skin contact flush with large amounts of water. Call a physician if irritation persists.

Inhalation: Immediately remove from further exposure. Give supplemental oxygen, if breathing is difficult. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

Ingestion: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. If swallowed, do NOT induce vomiting. Give a glass of water. Never give anything by mouth to an unconscious person.

Note to physician: If the product is ingested, treat the affected person symptomatically.

## SECTION 5 FIRE FIGHTING MEASURES

FLASH POINT (method used): -142°F (-97°C) (TCC) LOWER EXPLOSIVE LIMIT: 1.8% UPPER EXPLOSIVE LIMIT: 9.5%

EXTINGUISHING MEDIA: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>). Appropriate for surrounding fire.

UNUSUAL FIRE & EXPLOSION HAZARDS: None

SPECIAL FIRE FIGHTING PROCEDURES: As in any fire, wear pressure-demand self-contained breathing apparatus, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions: Isolate area. Keep unnecessary personnel away. Stay upwind. Keep out of low areas. Ventilate spaces before entering.

Environmental precautions: Prevent further leakage or spillage if safe to do so.

Methods for containment: Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up: Eliminate ignition sources including sources of electrical, static or frictional sparks. Wear appropriate protective equipment and clothing during clean-up.

Small Spills: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for disposal.

Large Spills: Dike far ahead of liquid spill for later disposal. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

## SECTION 7 HANDLING AND STORAGE

Handling: Avoid breathing mist. Avoid contact with skin and eyes. Wear suitable protective clothing. Wash hands after handling.

Storage: Product is extremely flammable. Do not store near heat or ignition sources. Do Keep from freezing. Keep containers tightly closed.

## SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits: NE

Personal protective equipment:

Gloves: Wear impervious gloves.

Eye/Face Protection: Wear safety glasses or goggles.

Skin Protection: Wear clothing suited to the task being performed.

Respiratory Protection: Not normally required if good ventilation is maintained.

## SECTION 9 PHYSICAL and CHEMICAL PROPERTIES

|                        |                               |                                     |                        |
|------------------------|-------------------------------|-------------------------------------|------------------------|
| BOILING POINT:         | -40° to 279°F (-40° to 137°C) | SPECIFIC GRAVITY (H2O=1):           | 0.7                    |
| VAPOR PRESSURE:        | NA                            | PERCENT VOLATILE BY VOL %:          | NA                     |
| VAPOR DENSITY (air=1): | 4.0                           | EVAPORATION RATE (Butyl Acetate=1): | >1                     |
| SOLUBILITY IN WATER:   | Nil                           | APPEARANCE & ODOR:                  | Yellow Paint / Solvent |
| pH:                    | NA                            |                                     |                        |

## SECTION 10 STABILITY and REACTIVITY DATA

STABILITY: Stable under normal conditions.

INCOMPATIBILITY (material to avoid): Strong acids or oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide, Oxides of Chromium and Lead, and low molecular weight hydrocarbons may be produced.

HAZARDOUS POLYMERIZATION: Will not occur

## SECTION 11 TOXICOLOGICAL INFORMATION

Components Test Results: No data available. Product may be irritating to eyes and skin.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

## SECTION 12 ECOLOGICAL INFORMATION

No Data Available.

## SECTION 13 DISPOSAL CONSIDERATIONS

Disposal instructions: Dispose according to all applicable Federal, State, and Local regulations.

## SECTION 14 TRANSPORT INFORMATION

T.D.G. Classification: Consumer commodity (Aerosols, UN1950, Class 2.1)

D.O.T. Classification: Consumer commodity, ORM-D

## SECTION 15 REGULATORY INFORMATION

US federal regulations: All components are listed in the United States TSCA Regulations.

CERCLA (Superfund) reportable quantity: None

SARA (Superfund Amendments and Reauthorization Act of 1986):

313 Components: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Section 302 extremely hazardous substance: No  
Section 311 hazardous chemical: No

Canada: This Product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.

|                                     |
|-------------------------------------|
| <b>SECTION 16 OTHER INFORMATION</b> |
|-------------------------------------|

Further information: (HMIS<sup>®</sup> is a registered trade and service mark of the NPCA.)

|                           |  |
|---------------------------|--|
| HMIS <sup>®</sup> ratings | Health: 2<br>Flammability: 4<br>Physical hazard: 0 |
| NFPA ratings              | Health: 2<br>Flammability: 4<br>Instability: 0     |

Other: NA-Not Applicable, ND-Not Determined, NE-Not Established.

Disclaimer Terms and Conditions. This SDS is designed only as guidance for the products to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantability or fitness for particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.

PREPARED: 11/23/93

UPDATED: 9/6/13

PRODUCT #: C1601-14