



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product ID: 156.268M100
Product Name: ZONEMARK I/E LTX WHT
Product Use: Paint product.
Print date: 25/Jun/2013
Revision Date: 25/Jun/2013

Company Identification

The Valspar Corporation - Architectural Coatings Division
1191 Wheeling Road
Wheeling, IL 60090

Manufacturer's Phone: 1-847-520-8580

24-Hour Medical Emergency Phone: 1-888-345-5732

2. HAZARDS IDENTIFICATION

Primary Routes of Exposure:

Inhalation
Ingestion
Skin absorption

Eye Contact:

None known.

Skin Contact:

None known.

Ingestion:

None known.

Inhalation:

- May cause irritation of respiratory tract.

This product contains ingredients that may contribute to the following potential chronic health effects:

- Prolonged breathing of mica dust may produce pneumoconiosis.

Carcinogens:

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

| Ingredient Name CAS-No. | Approx. Weight % | Chemical Name |
|------------------------------------|-----------------------------|----------------------|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | Titanium dioxide |
| PROPRIETARY INERT | 1 - 5 | PROPRIETARY INERT |

If this section is blank there are no hazardous components per OSHA guidelines.

4. FIRST AID MEASURES

Eye Contact:

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

Skin Contact:

Wash off with plenty of water.

Ingestion:

Get medical attention if symptoms occur

Inhalation:

Move to fresh air. Get medical attention, if symptoms develop or persist.

Medical conditions aggravated by exposure:

Any respiratory or skin condition.

5. FIRE FIGHTING MEASURES

| | |
|----------------------------------|--|
| Flash point (Fahrenheit): | 205 |
| Flash point (Celsius): | 96 |
| Lower explosive limit (%): | not determined |
| Upper explosive limit (%): | not determined |
| Autoignition temperature: | not determined |
| Sensitivity to impact: | no |
| Sensitivity to static discharge: | Sensitivity to static discharge is not expected. |
| Hazardous combustion products: | See Section 10. |

Unusual fire and explosion hazards:

None known.

Extinguishing media:

Carbon dioxide, dry chemical, foam and/or water fog.

Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

6. ACCIDENTAL RELEASE MEASURES

Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

7. HANDLING AND STORAGE

Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

Personal Protective Equipment

Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

Skin protection:

Appropriate chemical resistant gloves should be worn.

Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

Ventilation

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas.

Exposure Guidelines

OSHA Permissible Exposure Limits (PEL's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA (final) | Ceilings limits (final) | Skin designations |
|--------------------------------|---------------------|--|-------------------------|-------------------|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | 15 mg/m ³ TWA dust total | | |
| PROPRIETARY INERT | 1 - 5 | 20 mppcf (<1% crystalline silica) | | |

ACGIH Threshold Limit Value (TLV's)

| Ingredient Name CAS-No. | Approx. Weight % | TWA | STEL | Ceiling limits | Skin designations |
|--------------------------------|---------------------|--|------|----------------|----------------------|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | 10 mg/m ³ TWA | | | |
| PROPRIETARY INERT | 1 - 5 | 3 mg/m ³ TWA respirable fraction | | | |

9. PHYSICAL PROPERTIES

Odor:

Normal for this product type.

Physical State:

liquid

pH:

not determined

9. PHYSICAL PROPERTIES

| | |
|---|-----------------------|
| Vapor pressure: | 24 mmHg @ 77°F (25°C) |
| Vapor density (air = 1.0): | 0.6 |
| Boiling point: | 212°F (100°C) |
| Solubility in water: | not determined |
| Coefficient of water/oil distribution: | not determined |
| Density (lbs per US gallon): | 11.74 |
| Evaporation rate (butyl acetate = 1.0): | 0.1 |
| Flash point (Fahrenheit): | 205 |
| Flash point (Celsius): | 96 |
| Lower explosive limit (%): | not determined |
| Upper explosive limit (%): | not determined |
| Autoignition temperature: | not determined |

10. STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Stable under normal conditions. |
| Conditions to Avoid: | None known. |
| Incompatibility: | Strong oxidizing agents |
| Hazardous Polymerization: | None anticipated. |
| Hazardous Decomposition Products: | Carbon monoxide and carbon dioxide. Metal oxide fumes. |

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

11. TOXICOLOGICAL INFORMATION

| Ingredient Name CAS-No. | Approx. Weight % | NIOSH - Selected LD50s and LC50s |
|--------------------------------|---------------------|----------------------------------|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | > 10000 mg/kg Oral LD50 Rat |

Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

Contains TIO2 which is listed by IARC as a possible human carcinogen (Group 2B) based on animal data. Neither long term animal studies, nor human epidemiology studies of workers exposed to TIO2 provide an adequate basis to conclude TIO2 is carcinogenic. TIO2 is not classified as a carcinogen by NTP, U.S. OSHA, or the U.S. EPA.

| Ingredient Name CAS-No. | Approx. Weight % | IARC Group 1 - Human Evidence | IARC Group 2A - Limited Human Data | IARC Group 2B - Sufficient Animal Data |
|--------------------------------|---------------------|----------------------------------|---------------------------------------|---|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | | | Monograph 47 [1989] |

| Ingredient Name CAS-No. | Approx. Weight % | OSHA - Hazard Communication Carcinogens | OSHA - Specifically Regulated Carcinogens | ACGIH Carcinogens |
|--------------------------------|---------------------|---|--|-------------------|
| TITANIUM DIOXIDE 13463-67-7 | 15 - 20 | Present | | |

12. ECOLOGICAL DATA

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation

UN ID Number (msds):

NRPAIN

Proper Shipping Name:

PAINT, NOT REGULATED

U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Reportable Quantity Description:

International Air Transport Association (IATA):

Proper shipping name:

NOT REGULATED

International Maritime Organization (IMO):

Proper shipping name:

NOT REGULATED

Marine Pollutant

No

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

SARA 311/312 Hazard Class:

Acute: yes

Chronic: yes

Flammability: no

Reactivity: no

Sudden Pressure: no

U.S. STATE REGULATIONS:

Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

Pennsylvania Right To Know:

PROPRIETARY INERT

Trade Secret

TITANIUM DIOXIDE

13463-67-7

Additional Non-Hazardous Materials

PROPRIETARY INERT

Trade Secret

PROPRIETARY INGREDIENT

Trade Secret

PROPRIETARY RESIN

Trade Secret

Rule 66 status of product

Not photochemically reactive.

INTERNATIONAL REGULATIONS - Chemical Inventories

US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List:

Not all components in this product are listed on the Domestic Substances List.

16. OTHER INFORMATION**HMIS Codes**

| | |
|----------------------|--|
| Health: | 1* |
| Flammability: | 0 |
| Reactivity: | 1 |
| PPE: | X - See Section 8 for Personal Protective Equipment (PPE). |

Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

Preparation Information:

| | |
|----------------|-------------------------------|
| Prepared By: | Regulatory Affairs Department |
| Print date: | 25/Jun/2013 |
| Revision Date: | 25/Jun/2013 |