

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Rust Stop Enamel Machine & Implement John Deere Green

Product Code Identification Number: 225A133

MSDS Number:

GENERAL USE: Protective Coating

PRODUCT DESCRIPTION: Solvent base alkyd coating, hydrocarbon odor



MANUFACTURER'S NAME

Ace Hardware Paint Division

DATE PREPARED: October 26, 2005

SUPERSEDES: February 20, 2002

Page 1 of 4

ADDRESS (NUMBER, STREET, P.O. BOX)

21901 South Central Avenue

TELEPHONE NUMBER FOR INFORMATION

(800) 311-8324

(CITY, STATE AND ZIP CODE)

Matteson, IL 60443-2800

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

DISTRIBUTOR'S NAME

Ace Hardware Corporation

ADDRESS (NUMBER, STREET, P.O. BOX)

2200 Kensington Court

TELEPHONE NUMBER FOR INFORMATION

(800) 311-8324

(CITY, STATE AND ZIP CODE)

Oak Brook, IL 60523-2100

COUNTRY

USA

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	CAS #	%	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M3	PPM	MG/M3		
Petroleum distillate, aliphatic	64742-47-8	10 -30	100	525				
Petroleum distillate, aliphatic	64742-88-7	10 - 30	500	2000				
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	1 - 5	500	2900	100	525		
Chromium (III) oxide (a)	1308-38-9	3 - 7		0.5		0.5	Yes	

(a) See Section 15

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Green liquid, potentially hazardous vapors. Flammable as defined by DOT and TDG for Air / Ocean transport. Classified by DOT as Combustible for ground transport in containers less than 120 gallons. Classified as Combustible by OSHA. Can cause serious or fatal complications if swallowed. Can cause eye and skin irritation upon contact. Inhalation of vapors can cause anesthetic effect leading to death in poorly ventilated areas. Hazard symbols for this product - Xn; Risk Phrases - R 10, 20/22, 36/38

POTENTIAL HEALTH EFFECTS

INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.

SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.

EYES: High vapor concentration or contact may cause irritation and discomfort.

INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

MATERIAL SAFETY DATA SHEETPRODUCT NAME: Rust Stop Enamel Machine & Implement John Deere Green
October 26, 2005

Page 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

105° F (PMCC)

FLAMMABLE LIMITS

LEL: 0.5%

UEL: 6.0%

AUTOIGNITION TEMPERATURE: Not determined

NFPA CLASS: II

GENERAL HAZARDS: Product is considered combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

EXTINGUISHING MEDIA

Carbon dioxide, water fog, dry chemical, chemical foam

FIRE FIGHTING PROCEDURES

Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers can explode due to buildup of pressure when exposed to extreme heat. Do not use direct stream of water on pool fires as product may reignite on water surface. Caution - Material is combustible!

HAZARDOUS COMBUSTION PRODUCTS

Smoke, fumes, oxides of carbon

SECTION 6 - ENVIRONMENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COMBUSTIBLE - Evacuate and ventilate area; remove all sources of sparks, ignition and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: This material is combustible. It should be stored in tightly closed containers in a cool, well ventilated area. Vapor may form explosive mixtures in air. All sources of ignition should be controlled. This material may be classified as COMBUSTIBLE by DOT unless transported by vessel or aircraft. Refer to 49 CFR 173.120. Keep this and other chemicals out of reach of children. Avoid inhaling concentrated fumes or vapors.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**ENGINEERING CONTR0LS**

The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment. See Section 2 for Component Exposure Guidelines.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.

PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.

EYE PROTECTION: Safety goggles with side shields

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Rust Stop Enamel Machine & Implement John Deere Green
 October 26, 2005

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE (MM Hg) 3.4 mm Hg @ 20 ° C	VAPOR DENSITY (AIR = 1) > 1
SPECIFIC GRAVITY (WATER = 1) 1.193	EVAPORATION RATE (WATER = 1) < 1
SOLUBILITY IN WATER Negligible	FREEZING POINT Not determined
pH Not applicable	APPEARANCE AND ODOR Green viscous liquid, hydrocarbon odor
BOILING POINT 298°F (148° C)	PHYSICAL STATE Liquid
VISCOSITY (KREBS) 77 - 83	

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures, open flames
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Ingredients	CAS #	EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Petroleum distillate, aliphatic	64742-47-8	265-149-8	Not determined	Not determined
Petroleum distillate, aliphatic	64742-88-7	265-191-7	Not determined	Not determined
Stoddard solvent (Petroleum distillate, aliphatic)	8052-41-3	232-489-3	> 5000 mg / kg Oral - rat	> 5500 mg / m3 / 4H Inhalation - rat
Chromium (III) oxide (a)	1308-38-9	215-160-9	Not established	Not established

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce concentrated hazardous vapors or fumes in a disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for ignitable materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Paint

DOT HAZARD CLASS / Pack Group: 3 / III	IATA HAZARD CLASS / Pack Group: 3 / III
REFERENCE: 49 CFR 173.150, .173, .242	IMDG HAZARD CLASS: 3 / III
UN / NA IDENTIFICATION NUMBER: UN 1263	RID/ADR Dangerous Goods Code: 3 (3B)
LABEL: FLAMMABLE LIQUID	UN TDG Class / Pack Group: 3 / III
HAZARD SYMBOLS: F	Hazard Identification Number (HIN): 33

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EC, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Rust Stop Enamel Machine & Implement John Deere Green
 October 26, 2005

SECTION 15 - REGULATORY INFORMATION

TSCA (Toxic substance Control Act)

All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

SARA TITLE III (Superfund Amendments and Reauthorization Act)

311/312 Hazard Categories
 Immediate health, fire hazard

313 Reportable Ingredients:

(a) A "Yes" in the SARA TITLE III column in Section 2 indicates a toxic chemical subject to annual reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CERCLA (Comprehensive Response Compensation and Liability Act)

None

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986

There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

CPR (Canadian Controlled Products Regulations)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. WHMIS Classification: B3

DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List)

Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

EINECS (European Inventory of Existing Commercial Chemical Substances)

Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

EC Risk Phrases

R10 Flammable
 R20/22 Harmful by inhalation and if swallowed.
 R36/38 Irritating to eyes and skin.

SYMBOL(S) REQUIRED FOR LABEL

Harmful



EC Safety Phrases

S23 Do not breathe vapor
 S25 Avoid contact with eyes
 S28 After contact with skin, wash immediately with plenty of soap and water.
 S29 Do not empty into drains

SECTION 16 - OTHER INFORMATION

No specific notes.

HMIS HAZARD RATINGS

HEALTH	1	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	2	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	0	1 = SLIGHT	4 = EXTREME

REVISION SUMMARY:

This MSDS has been revised in the following sections:
 Section 14, DOT Classification

MSDS Prepared by: Comprehensive Data Base, Inc.
 P.O. Box 5604
 Lakeland, FL 33807 USA
 (863) 644 - 3298 www.compdatabase.com

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.