

Material Safety Data Sheet



Alum

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Alum

OTHER/GENERIC NAMES: Aluminum Sulfate

PRODUCT USE: Water treatment. Various industrial uses.

MANUFACTURER: General Chemical Corporation
90 East Halsey Road
Parsippany, NJ 07054

FOR MORE INFORMATION CALL: 973-515-1840
(Monday-Friday, 9:00am-4:30pm)

IN CASE OF EMERGENCY CALL: 800-631-8050
(24 Hours/Day, 7 Days/Week)

2. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>INGREDIENT NAME</u> | <u>CAS NUMBER</u> | <u>WEIGHT %</u> |
|------------------------|---------------------------|-----------------|
| Aluminum sulfate | 10043-01-3 (anhydrous) | 100 |

Trace impurities and additional material names not listed above may also appear in Section 15 towards the end of the MSDS. These materials may be listed for local "Right-To-Know" compliance and for other reasons.

OSHA Hazard Communication Standard: *This product is considered hazardous under the OSHA Hazard Communication Standard.*

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: White or creamy white granules or powder with no odor. Can irritate the skin and eyes. Not flammable, but may release toxic vapors if decomposed in a fire.

POTENTIAL HEALTH HAZARDS

SKIN: May cause skin irritation, especially under repeated or prolonged contact, or when moisture is present.

EYES: May irritate or burn the eyes. Similarly for the aqueous solution.

INHALATION: Dust or mist inhalation at levels above the TLV may cause irritation to the respiratory tract.

INGESTION: May irritate the gastrointestinal tract.

DELAYED EFFECTS: None known.

Ingredients found on one of the three OSHA designated carcinogen lists are listed below.

| <u>INGREDIENT NAME</u> | <u>NTP STATUS</u> | <u>IARC STATUS</u> | <u>OSHA LIST</u> |
|--|-------------------|--------------------|------------------|
| No ingredients listed in this section. | | | |

MATERIAL SAFETY DATA SHEET

Dry Alum

4. FIRST AID MEASURES

SKIN: Flush with plenty of soap water, removing contaminated clothing. If irritation develops, get medical attention.

EYES: Immediately flush with water, continuing for at least 15 minutes. If irritation persists, get medical attention.

INHALATION: Promptly remove to fresh air.

INGESTION: If conscious, immediately give large quantity of water or milk. If not already vomiting, induce vomiting by touching finger to back of throat. Get medical assistance.

ADVICE TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

| | |
|---|----------------|
| FLASH POINT: | Not flammable |
| FLASH POINT METHOD: | Not applicable |
| AUTOIGNITION TEMPERATURE: | Not applicable |
| UPPER FLAME LIMIT (volume % in air): | Not applicable |
| LOWER FLAME LIMIT (volume % in air): | Not applicable |
| FLAME PROPAGATION RATE (solids): | Not applicable |
| OSHA FLAMMABILITY CLASS: | Not applicable |

EXTINGUISHING MEDIA:

Product is not flammable. Use any extinguishing agent suitable for surrounding fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None.

SPECIAL FIRE FIGHTING PRECAUTIONS/INSTRUCTIONS:

Use self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR OTHER RELEASE: (See section 8 for recommended personal protective equipment.)

Shovel up dry chemical and place in empty container and cover. Spray residue with plenty of water. Neutralize any further residue with alkali such as soda ash, lime or limestone. Adequate ventilation is required if soda ash or limestone is used, because of the consequent release of carbon dioxide gas. Collect liquid and/or residue and dispose of in accordance with applicable regulations.

Spills and releases may have to be reported to Federal and/or local authorities. See Section 15 regarding reporting requirements.

7. HANDLING AND STORAGE

NORMAL HANDLING: (See section 8 for recommended personal protective equipment.)

Avoid contact with skin, eyes and clothing. Do not breathe product dusts or mists.

MATERIAL SAFETY DATA SHEET

Dry Alum

STORAGE RECOMMENDATIONS:

Store in a cool, dry area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use local exhaust if dusty or misty conditions prevails.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION: Wear gloves and appropriate industrial work clothing including long sleeved shirts and trousers for routine product handling. Full impervious clothing is recommended if handling solutions and there is repeated or prolonged contact.

EYE PROTECTION: Wear chemical safety goggles. Do not wear contact lenses.

RESPIRATORY PROTECTION: A NIOSH approved dust or mist respirator should be worn in areas where product dusts or mists are present.

ADDITIONAL RECOMMENDATIONS: The presence of an eyewash and safety shower is recommended.

EXPOSURE GUIDELINES

| <u>INGREDIENT NAME</u> | <u>ACGIH TLV</u> | <u>OSHA PEL</u> | <u>OTHER LIMIT</u> |
|--------------------------------|---------------------|---------------------|--------------------|
| Aluminum sulfate (as Aluminum) | 2 mg/m ³ | 2 mg/m ³ | None |

¹ = Limit established by General Chemical Corporation.

² = Workplace Environmental Exposure Level (AIHA).

³ = Biological Exposure Index (ACGIH).

OTHER EXPOSURE LIMITS FOR POTENTIAL DECOMPOSITION PRODUCTS:

None

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: White or creamy white granules or powder.

PHYSICAL STATE: Solid

MOLECULAR WEIGHT: ~594 for Al₂(SO₄)₃·14H₂O

CHEMICAL FORMULA: Al₂(SO₄)₃·14H₂O

ODOR: Odorless

SPECIFIC GRAVITY (water = 1.0): 1.61

SOLUBILITY IN WATER (weight %): 50% at 0°C

pH: ~3.5 (1% solution)

BOILING POINT: Not applicable

MELTING POINT: Not applicable

MATERIAL SAFETY DATA SHEET

Dry Alum

VAPOR PRESSURE: Negligible
VAPOR DENSITY (air = 1.0): Not applicable
EVAPORATION RATE: Not applicable **COMPARED TO:** Not applicable.
% VOLATILES: Not applicable
FLASH POINT: Not flammable
(Flash point method and additional flammability data are found in Section 5.)

10. STABILITY AND REACTIVITY

NORMALLY STABLE? (CONDITIONS TO AVOID):

Normally stable. Avoid temperatures above 760°C, as this will yield toxic and corrosive gases.

INCOMPATIBILITIES:

Alkalis and water reactive materials such as oleum: causes exothermic reactions.

HAZARDOUS DECOMPOSITION PRODUCTS:

At elevated temperatures, sulfur oxides may be formed. These are toxic and corrosive and are oxidizers. Sulfur trioxide is also a fire hazard. The loss of these gases leaves a caustic residue.

HAZARDOUS POLYMERIZATION:

Will not occur

11. TOXICOLOGICAL INFORMATION

IMMEDIATE (ACUTE) EFFECTS:

Aluminum sulfate:

LD₅₀ (oral, mouse): 6207 mg/kg

LD₅₀ (oral, rat): 1930 mg/kg

DELAYED (SUBCHRONIC AND CHRONIC) EFFECTS:

Data not available

OTHER DATA:

None

12. ECOLOGICAL INFORMATION

Aluminum sulfate:

14 ppm/36 hr/ fundulus/fatal/fresh water.

240 ppm/48 hr/mosquito fish/TL_m/water type not specified.

TL_m Mosquito fish, 235 ppm, 96 hours

LC₅₀ Largemouth bass, 250 ppm, 96 hours

MATERIAL SAFETY DATA SHEET
Dry Alum

13. DISPOSAL CONSIDERATIONS

RCRA

Is the unused product a RCRA hazardous waste if discarded? No

If yes, the RCRA ID number is: Not applicable

OTHER DISPOSAL CONSIDERATIONS:

If permitted by regulations, material may be dissolved in water and neutralized with alkali. Neutralized waste may have to be disposed of by an approved contractor.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

US DOT HAZARD CLASS: 9 (only if greater than 8700 lbs. in one package)

US DOT ID NUMBER: UN3077

PROPER SHIPPING NAME: Environmentally hazardous substances, solid, n.o.s. (contains aluminum sulfate)

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

15. REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT (TSCA)

TSCA INVENTORY STATUS: All ingredients listed on the TSCA Inventory

OTHER TSCA ISSUES: None

SARA TITLE III/CERCLA

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

| <u>INGREDIENT NAME</u> | <u>SARA/CERCLA RQ (lb)</u> | <u>SARA EHS TPQ (lb)</u> |
|-------------------------------|-----------------------------------|---------------------------------|
| Aluminum sulfate (anhydrous) | 5000 (*as is 8700 lbs.) | None |

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

SECTION 311 HAZARD CLASS: Immediate

SARA 313 TOXIC CHEMICALS:

MATERIAL SAFETY DATA SHEET
Dry Alum

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percents are found in Section 2.

INGREDIENT NAME

COMMENT

No ingredients listed in this section.

STATE RIGHT-TO-KNOW

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

INGREDIENT NAME

WEIGHT %

COMMENT

No ingredients listed in this section.

ADDITIONAL REGULATORY INFORMATION:

None listed

WHMIS CLASSIFICATION (CANADA):

Class D2B.

Classified in accordance with WHMIS Controlled Product regulations.

FOREIGN CHEMICAL CONTROL INVENTORY STATUS:

All ingredients listed on Canadian DSL.

16. OTHER INFORMATION

CURRENT ISSUE DATE: June, 2001

PREVIOUS ISSUE DATE: December, 1993

CHANGES TO MSDS FROM PREVIOUS ISSUE DATE ARE DUE TO THE FOLLOWING:

Updated to ANSI format.

OTHER INFORMATION: None