

MANUFACTURER
Castle Products, Inc.
424 St. Paul Street
Rochester, NY 14605
1-800-876-0222
EMERGENCY (585) 275-3232

MATERIAL SAFETY DATA SHEET

Hazard: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme.
Protection: A-Goggles, B-Goggles & gloves,
C-Goggles, gloves, & protective wear.
Other: NA-Not Applicable, ND-Not Determined,
NE-Not Established.

HAZARD RATING
Health 2
Fire 4
Reactivity 0
Protection B

SECTION I DESCRIPTION

TRADE NAME: **Castle® Rubberized Undercoating™**

PRODUCT TYPE: Abrasion-Resistant Undercoat

SECTION II HAZARDOUS INGREDIENTS

INGREDIENT	CAS #	PEL	TLV	STEL	%
Toluene	108-88-3	NE	50 ppm	NE	30-60 %
Acetone	67-64-1	NE	NE	NE	5-10 %
Calcium Carbonate	1317-65-3	NE	NE	NE	5-10 %
Synthetic Rubber	Proprietary	NE	NE	NE	5-10 %
Isobutane	75-28-5	NE	NE	NE	5-10 %
Propane	74-98-6	NE	1000 ppm	NE	10-30 %

SECTION III PHYSICAL DATA

BOILING POINT:	NE	SPECIFIC GRAVITY (H ₂ O=1):	0.92 – 0.96 (liquid by weight)
VAPOR PRESSURE:	55-65	PERCENT VOLATILE BY VOL %:	NE
VAPOR DENSITY (air=1):	Greater than 1	EVAPORATION RATE (Butyl Acetate=1):	Greater than 1
SOLUBILITY IN WATER:	Negligible	APPEARANCE & ODOR:	Black / Aromatic

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (method used): 4.4°C (TCC) LOWER EXPLOSIVE LIMIT: 1.2 % UPPER EXPLOSIVE LIMIT: 7.1 %
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, or foam.
UNUSUAL FIRE & EXPLOSION HAZARDS: Extremely flammable, particularly under conditions of excessive heat, sparks, and open flame. Heated cans may burst.
SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment, including self-contained breathing apparatus, should be worn in a fire involving this material. Water from fogging nozzles may be used to cool closed containers to prevent pressure build-up if exposed to extreme temperatures.

SECTION V HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Eye contact, skin contact, inhalation, and ingestion.
EFFECTS OF OVEREXPOSURE: • Eyes: May cause irritation. • Skin: May cause irritation. Chronic exposure may cause defatting and/or dermatitis.
• Inhalation: Inhalation of solvents may cause irritation. Propellant is a simple asphyxiant. • Ingestion: May cause headache, nausea, vomiting, and weakness.
EMERGENCY & FIRST AID PROCEDURES: • Eyes: Flush with plenty of water for at least 15 minutes and get medical attention. • Skin: Wash thoroughly with soap and water. • Inhalation: Remove to fresh air. • Ingestion: Do not induce vomiting. Get immediate medical attention.

SECTION VI REACTIVITY DATA

STABILITY: Stable under normal conditions.
INCOMPATIBILITY (materials to avoid): Strongly oxidizing agents.
HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.
HAZARDOUS DECOMPOSITION PRODUCTS: In fire, will decompose to hydrocarbon fumes and smoke and carbon monoxide where combustion is incomplete.

SECTION VII SPILL OR LEAK PROCEDURES

IF RELEASED OR SPILLED: Remove all sources of ignition. Use inert absorbent material and non-sparking tools. Avoid breathing fumes. Ventilate area. Prevent from entering watercourses.
WASTE DISPOSAL METHOD: Do not puncture or incinerate even when empty. Dispose of in accordance with federal, state, and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION: LOCAL XXXXX MECHANICAL (if used indoors on a continuous basis) OTHER
RESPIRATORY PROTECTION: If used indoors on a continuous basis, use of a cartridge type respirator (NIOSH / MSHATC 23C or equivalent) is recommended.
EYE PROTECTION: Safety goggles.
PROTECTIVE GLOVES: Chemical resistant gloves.
OTHER PROTECTIVE EQUIPMENT: Long sleeves and long pants.

SECTION IX SPECIAL PRECAUTIONS

HANDLING & STORING PRECAUTIONS: Store in a cool, well-ventilated area not to exceed 50°C. Keep away from heat, sparks, or open flame.

PREPARED: 09/25/93

UPDATED: 12/31/06

PRODUCT #: C2402