



MATERIAL SAFETY DATA SHEET

SPRAYPAK BASEBOARD & WAX STRIPPER

1. Product And Company Identification				
Supplier Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com		Manufacturer Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com		
Supplier Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924		Manufacturer Emergency Contacts & Phone Number Chem-Tel: 1-800-255-3924		
Issue Date: 07/24/2008 Product Name: SPRAYPAK BASEBOARD & WAX STRIPPER Chemical Name: 7-7903-2 CAS Number: Not Established MSDS Number: 4315 Product Code: 433-4112-6 Product/Material Uses - Baseboard and Wax Stripper				
2. Composition/Information On Ingredients				
		Ingredient Name	CAS Number	Percent Of Total Weight
		2-BUTOXYETHANOL	111-76-2	5 - 10
		ISOBUTANE	75-28-5	
		MONOETHANOLAMINE	141-43-5	
		PROPANE	74-98-6	
Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinogens are listed when present at 0.1% or greater.				
3. Hazards Identification				
Primary Routes(s) Of Entry - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. Eye Hazards - Irritant to eyes. It may cause tearing, redness and swelling of the eyes. Skin Hazards - Irritant to skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may result on skin absorption of potentially harmful amounts. Ingestion Hazards - Harmful if swallowed. This is an aerosol product, ingestion is unlikely to occur. Inhalation Hazards - Over inhalation of vapor or mist may cause severe irritation to the nose, throat and respiratory tract. Chronic/Carcinogenicity Effects - 2-Butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage. Teratogenicity (Birth Defects) - Not known Reproductive Effects - Not known Neurotoxicity - No available information Mutagenicity (Genetic Effect) - No available information				

MATERIAL SAFETY DATA SHEET

SPRAYPAK BASEBOARD & WAX STRIPPER


3. Hazards Identification - Continued

Signs And Symptoms - Acute: Inhalation of vapor or mist may cause headaches, dizziness and nausea. May irritate the respiratory tract system. Contact with skin causes irritation. Contact with the eyes causes irritation.

Conditions Aggravated By Exposure - May aggravate pre-existing skin and respiratory disorders.

Conditions Aggravated By Overexposure - May aggravate pre-existing skin and respiratory disorders.

First Aid (Pictograms)



4. First Aid Measures

Eye - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin - Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

Ingestion - Ingestion from an aerosol product is unlikely to occur. In case of accidental ingestion, call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

Inhalation - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

5. Fire Fighting Measures

Flash Point: Not available °F Not available °C

Flash Point Method: Not available

Lower Explosive Limit: Not available

Upper Explosive Limit: Not available

Fire And Explosion Hazards - This product is an aerosol product for which **Flame Projection is 0 in.** Temperatures above 120 F may cause cans to burst.

Extinguishing Media - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

Fire Fighting Instructions - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

7. Handling And Storage

Handling And Storage Precautions - Store in a cool, dry place away from heat and open flame.

Handling Precautions - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Keep out of reach of children.

Storage Precautions - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL I (NFPA-30B)**

Work/Hygienic Practices - Wash hands with soap and water after handling.

MATERIAL SAFETY DATA SHEET

SPRAYPAK BASEBOARD & WAX STRIPPER

Protective Clothing (Pictograms)



8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general or local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

Skin Protection - Rubber, vinyl or household type gloves required.

Respiratory Protection - Use in well-ventilated area ONLY. **When using indoors, keep windows and doors open until fumes disipate.**

Ingredient(s) - Exposure Limits

2-BUTOXYETHANOL

ACGIH TLV-TWA 20 ppm (Skin) ; OSHA PEL-TWA 50 ppm (Skin)

MONOETHANOLAMINE

OSHA PEL 3 ppm ; ACGIH TLV 3 ppm

PROPANE

ACGIH TLV-TWA 1000 ppm ; OSHA PEL-TWA 1,000 ppm

9. Physical And Chemical Properties

Appearance - Yellow clear liquid

Odor - Minty

Chemical Type: Mixture

Physical State: Liquid

Melting Point: Not applicable °F Not applicable °C

Boiling Point: Water 212 °F Water 100 °C

Specific Gravity: 1.0 concentrate

Percent VOCs: 18.3

pH Factor: 10.5 to 11.5

Solubility: Soluble in water

Evaporation Rate: Faster than butyl acetate

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

Incompatible Materials - Avoid heat and open flame.

Hazardous Decomposition Products - Thermal decomposition may yield gases like ammonia, carbon monoxide, carbon dioxide and nitrogen oxides.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

11. Toxicological Information

See Section 3. "Hazards Identification"

MATERIAL SAFETY DATA SHEET

SPRAYPAK BASEBOARD & WAX STRIPPER

12. Ecological Information

Ecotoxicological Information - No specific ecological data is available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

14. Transport Information

Proper Shipping Name - ORM-D Consumer Commodity

Hazard Class

2.1

DOT Identification Number

UN1950

DOT Shipping Label

Aerosol Consumer Commodity

15. Regulatory Information

U.S. Regulatory Information - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

SARA Section 313 Notification - This product contains the following toxic chemicals (above the *de minimis* level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material: 2-Butoxyethanol. See section 2 for % amount in this product.

Ingredient(s) - U.S. Regulatory Information

2-BUTOXYETHANOL

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

Ingredient(s) - State Regulations

2-BUTOXYETHANOL

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

ISOBUTANE


New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

MATERIAL SAFETY DATA SHEET

SPRAYPAK BASEBOARD & WAX STRIPPER

NFPA 	HMIS <table border="1"><tr><td>HEALTH</td><td>*2</td></tr><tr><td>FLAMMABILITY</td><td>2</td></tr><tr><td>REACTIVITY</td><td>1</td></tr><tr><td>PERSONAL PROTECTION</td><td>B</td></tr></table>	HEALTH	*2	FLAMMABILITY	2	REACTIVITY	1	PERSONAL PROTECTION	B
HEALTH	*2								
FLAMMABILITY	2								
REACTIVITY	1								
PERSONAL PROTECTION	B								

16. Other Information

Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 07/16/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.

Printed Using MSDS Generator™ 2000