

## MATERIAL SAFETY DATA SHEET

### E-Z PAINT THINNER

EMERGENCY CONTACT: FOR CHEMICAL EMERGENCY - SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT  
CALL CHEMTREC AT 1-800-424-9300, DAY OR NIGHT

<u>INDEX</u>	<u>HMIS</u>	<u>NFPA</u>
4 - Severe	Health 1	Health 1
3 - Serious	Flammability 2	Flammability 2
2 - Moderate	Physical Hazard 0	Reactivity 0
1 - Slight		
0 - Insignificant		

### Section 2. CHEMICAL AND PHYSICAL PROPERTIES

**CHEMICAL NAME:**

petroleum hydrocarbon

**FORMULA:**

not applicable

**HAZARDOUS DECOMPOSITION PRODUCTS:**

carbon monoxide and carbon dioxide from burning

**INCOMPATIBILITY (Keep away from):**

strong oxidizers such as hydrogen peroxide, bromine, and chromic acid

**HAZARDOUS INGREDIENTS:**

Stoddard Solvent

% (Volume)

100

CAS #

8052-41-3

Contains insitu ingredient(s) - for additional information, see environmental section IX

1,2,4 Trimethylbenzene

95-63-6

**FORM:**

liquid

**ODOR:**

mild petroleum

**APPEARANCE:**

low viscosity liquid

**COLOR:**

colorless

**SPECIFIC GRAVITY (water=1):**

0.77

**BOILING POINT:**

greater than 154 deg. C (310 deg. F)

**MELTING POINT:**

not applicable

**SOLUBILITY IN WATER (by weight %):**

0 at 20 deg. C

**EVAPORATION RATE:**

(n buytl acetate = 1) .2

**VAPOR PRESSURE (ASTM D2879, mm Hg at 20 deg. C):**

0.62

**VAPOR DENSITY (air = 1):**

4.85

**pH (as is):**

not applicable

STABILITY:

Product is stable under normal conditions

VISCOSITY SUS at 100 deg F:

Less than 100

---

Section 3. FIRE AND EXPLOSION DATA

---

SPECIAL FIRE FIGHTING PROCEDURES

Do not use water except as fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Do not cut, weld, braze, solder, drill, grind or expose containers, drums, tanks, etc. of product to heat, flame, sparks, static electricity or other sources of ignition; they may ignite explosively.

FLASHPOINT:

(Method Used) Tag closed-up                      43 deg. C                      (110 deg. F)

FLAMMABLE LIMITS %:

Lower: 1    Upper: 7

EXTINGUISHING AGENTS:

Drychemical or Waterfog or CO<sub>2</sub> or Foam

Closed containers exposed to fire may be cooled with water.

---

Section 4. HEALTH HAZARD DATA

---

PERMISSIBLE CONCENTRATIONS (air):

STODDARD SOLVENT                      (CAS# 8052-41-3)

500 ppm (OSHA PEL, TWA)

100 ppm (ACGIH TLV, TWA)

TRIMETHYLBENZENE

25 ppm, 125 mg/m<sup>3</sup>    (OSHA/ACGIH)

CHRONIC EFFECTS OF OVEREXPOSURE:

no data available

ACUTE TOXICOLOGICAL PROPERTIES:

for stoddard solvent: inhalation-irritation of eyes, nose and throat, dizziness; skin contact-dermatitis; eyes-irritation; ingestion-nausea, vomiting. Large amounts, if retained, lead to symptoms of central nervous system depression.

EMERGENCY FIRST AID PROCEDURES:

Eyes:                      Immediate flush with large quantities of water for at least 15 minutes and call a physician.

Skin Contact:                      Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation:                      Remove victim to fresh air. Call a physician.

If Swallowed:                      Call a physician immediately. DO NOT induce vomiting. (Vomiting may cause aspiration into lungs resulting in chemical pneumonia.)

ROUTES OF ENTRY:

Inhalation, skin/eye contact, ingestion

TARGET ORGAN(S):

Respiratory system, central nervous system, skin and eyes

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Preexisting eye, skin and respiratory disorders.

---

Section 5. SPECIAL PROTECTION INFORMATION

---

VENTILATION TYPE REQUIRED (Local, mechanical, special):

Local if necessary to maintain allowable PEL (permissible exposure limit) or TLV (threshold limit value)

RESPIRATORY PROTECTION (Specify type):

Use NIOSH/MSHA certified respirator with dual organic vapor/mist and particulates cartridge if vapor concentration exceeds permissible exposure limit.

PROTECTIVE GLOVES:

neoprene type

EYE PROTECTION:

chemical safety goggles

OTHER PROTECTIVE EQUIPMENT:

none

---

Section 6. HANDLING OF SPILLS OR LEAKS

---

PROCEDURES FOR CLEAN-UP:

Avoid all ignition sources such as flames and sparks. Insure good ventilation. If volume is significant, transfer into containers for disposal. Seal containers tightly. Absorb on an inert ingredient such as earth, sand or vermiculite. Sweep up and dispose of according to Federal, State and local regulations.

WASTE DISPOSAL:

Dispose of in accordance with all applicable federal, state and local regulations.

---

Section 7. SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid all ignition sources such as flames and sparks.  
Do not handle or store at temperatures over 38 deg. C (100 deg. F).  
Do NOT store in confined areas such as trailers.

MAXIMUM STORAGE TEMPERATURE:

38 deg. C (100 deg. F)

---

Section 8. TRANSPORTATION DATA

---

D. O. T.:

Regulated

U. S. D. O. T. PROPER SHIPPING NAME & [CONTAINER MODE]:

PAINT RELATED MATERIAL [55 Gal Drum/5 Gal Pail/2.5 Gallon/Gallon/Quart/Pint]

LABEL(S) REQUIRED:

none

REPORTABLE QUANTITY:

none

FREIGHT CLASSIFICATION :

Stoddard solvent-Combustible liquid

SPECIAL TRANSPORTATION NOTES:

DOMESTIC: Unregulated by DOT when shipped in containers of less than 118.9 gallons.  
FOR EXPORT: Regulated as Flammable Liquid, N. O. S., (Stoddard Solvent), 3.3, UN 1268, PG III, Category A, IMDG 3375.

OTHER TRANSPORT INFORMATION

The DOT Transport Information may vary with the container and mode of shipment.

---

Section 9. ENVIRONMENTAL/SAFETY REGULATIONS

---

SECTION 313 (TITLE III SUPERFUND AMENDMENT AND REAUTHORIZATION ACT):

This product contains the following chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (the corresponding CAS number and percent by weight are also provided):

1,2,4 trimethyl benzene	CAS # 95-63-6	2.67%
-------------------------	---------------	-------

---

---

COMMENTS

---

---

STATE REGULATORY INFORMATION:

PENNSYLVANIA WORKER AND COMMUNITY RIGHT TO KNOW ACT: This product contains the following ingredient(s) listed in Appendix A Hazardous Substance List:

<u>Component</u>	<u>CAS No.</u>
stoddard solvent	8052-41-3

The component(s) of this product are on the US TSCA Inventory and Canadian Domestic Substance List.

This product contains a chemical (or chemicals) known to the State of California to cause cancer, birth defects and/or other reproductive harm - Naphthalene @ 0.44% (vol).

WHMIS Classification: B3 - Combustible Liquid

---

---

LABEL INFORMATION

---

---

CAUTION! COMBUSTIBLE MIXTURE

Contains Stoddard Solvent - CAS No. 8052-41-3

Use wherever a Stoddard Solvent or Mineral Spirits is recommended. E-Z Paint Thinner does not contain any chlorinated solvent.

Use adequate ventilation to insure that fumes do not come in contact with sources of ignition such as flames and sparks. Avoid prolonged breathing of mist or vapors and prolonged or repeated skin contact. Use NIOSH/OSHA approved respirator, and chemical splash goggles to prevent eye contact.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush immediately with large amounts of water for a least 15 minutes. Call physician.

Skin Contact: Remove excess with cloth or paper. Wash thoroughly with soap and water.

Inhalation: Remove victim to fresh air. Call a physician. The OSHA permissible exposure limit for stoddard solvent is 500 ppm.

If Swallowed: Do not induce vomiting. Call a physician immediately.

E. E. Zimmerman Company/Elroy Turpentine Company believes that the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of their use.