

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

HEALTH 1 REACTIVITY 0
 FLAMMABILITY 3 PERSONAL PROTECTION A

IDENTITY (As Used on Label and List)
 A-323 Furniture Polish

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name International Distribution Systems, Inc.	Emergency Telephone Number 800-255-4564
Address (Number, Street, City, State, and ZIP Code) 910 3rd Street, Suite B	Telephone Number for Information 800-255-4564
Neptune Beach, Florida 32266	Date Prepared November 14, 1990
	Signature of Preparer (optional) Regulatory Dept.

Section II — Hazardous Ingredients/Identity Information N.E.-Not Established

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Isobutane (CAS No. 75-28-5)	800 ppm	800 ppm		
Propane (CAS No. 74-98-6)	1000 ppm	Asphixiant		
Petroleum solvent (CAS No. 64742-48-9)	N.E.	N.E.		

None of the compounds in this product are listed or present in concentrations requiring reporting under SARA Title III Sec 313. Refer to 40 CFR 372.

Any substance listed as hazardous by the states of California, Massachusetts, New Jersey and Pennsylvania are described above if known present in regulated concentrations.

Section III — Physical/Chemical Characteristics G.T.-Greater Than N.D.-No Data

Boiling Point (concentrate) - Initial	212°F	Specific Gravity (H ₂ O = 1)	0.903
Vapor Pressure (mm Hg) psig at 70°F	40±5	Melting Point	N.D.
Vapor Density (AIR = 1)	G.T.1	Evaporation Rate (Butyl Acetate = 1)	N.D.

Solubility in Water
 Emulsifiable pH 6.5±1

Appearance and Odor
 Opaque white liquid, lotion consistency, with lemon scent in an aerosol can.

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) USA Flame Projection- Flammable 30" No flashback Conc-45°	Flammable Limits	LEL N.D.	UEL N.D.
Extinguishing Media TCC-est.			

Carbon dioxide, dry chemical, foam. Treat as an oil fire.

Special Fire Fighting Procedures

Use waterspray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses. Wear SCBA in chemical fires.

Unusual Fire and Explosion Hazards

Aerosol container (pressurized) may burst if heated over 120°F. Flammable content

Section V — Reactivity Data

Stability	Unstable		Conditions to Avoid Extreme heat, direct sunlight.
	Stable	X	

Incompatibility (Materials to Avoid)

Strong oxidizers

Hazardous Decomposition or Byproducts

Carbon dioxide, carbon monoxide, aldehydes, silicone, dioxide, fumes, and smoke

Hazardous Polymerization	May Occur		Conditions to Avoid None known
	Will Not Occur	X	

Section VI — Health Hazard Data

Route(s) of Entry: Eyes	Inhalation? Yes	Skin? No	Ingestion? No
----------------------------	--------------------	-------------	------------------

Health Hazards (Acute and Chronic)

Warning. Flammable liquid and vapor. May cause eye irritation. Harmful or fatal if swallowed. Contains petroleum distillates. Repeated or prolonged occupational overexposure may lead to dermatitis.

Carcinogenicity: None known	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
--------------------------------	------------	------------------------	-----------------------

Signs and Symptoms of Exposure

Headache, dizziness, irritation of nose and throat, drowsiness, fatigue, loss of coordination. Redness, tearing, burning in eyes. Red, dry, cracking skin.

Medical Conditions

Generally Aggravated by Exposure Pre-existing skin disorders.

Emergency and First Aid Procedures

INGESTION-Do not induce vomiting. Call a physician or poison control center immediately. EYES-Flush with plenty of water for at least 15 minutes, then call a physician. SKIN-Wash thoroughly with soap and water. INHALATION-Get to fresh air.

Section VII — Precautions for Safe Handling and Use**Steps to Be Taken in Case Material Is Released or Spilled**

Isolate and ventilate area. Eliminate all ignition sources. Wear protective gear as necessary. Dike to prevent spread. Wipe up on rag or absorbent material. Place in suitable container for proper disposal or vacuum up for reclamation.

Waste Disposal Method

Consult local, state and federal regulations. Do not puncture or incinerate container. Replace cap on empty can, wrap, then discard if allowed by relevant statutes.

Precautions to Be Taken in Handling and Storing

Store in a cool (under 120°F) dry location away from heat, sparks, open flame, and direct sunlight. Direct spray away from face. Replace cap when not in use. Do not use around ignition source. Avoid inhaling mist and vapors.

Other Precautions

Follow label directions carefully. Keep out of reach of children. Avoid contact with eyes, skin, and clothing. Do not intentionally concentrate and inhale mist and vapors. Do not ingest.

Section VIII — Control Measures

Respiratory Protection (Specify Type) Not usually necessary. Use with adequate ventilation. Use NIOSH/MSHA respirator if PELs/TLVs are exceeded.

Ventilation	Local Exhaust Not usually necessary.	Special None
	Mechanical (General) Yes	Other None

Protective Gloves

Not usually necessary.

Eye Protection

Approved safety glasses or goggles.

Other Protective Clothing or Equipment

Not usually necessary. To prevent direct contact wear boots, apron, etc if

Work/Hygienic Practices

Normal. Wash thoroughly before eating, drinking, smoking, using restrooms, etc

While the information and recommendations set forth herein are believed to be accurate as of the date hereon, Dyson, Inc. makes no warranty with respect thereto and disclaims all liability from reliance thereon.