

MATERIAL SAFETY DATA SHEET

R00799  
01 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

|                     |   |                           |    |
|---------------------|---|---------------------------|----|
| PRODUCT NUMBER      | R00799  | HMIS CODES                |    |
|                     |   | Health                    | 2* |
|                     |   | Flammability              | 4  |
|                     |   | Reactivity                | 0  |
| PRODUCT NAME        | RUST TOUGH* Rust Preventive Enamel, Gloss Black |                           |    |
| MANUFACTURER'S NAME | THE SHERWIN-WILLIAMS COMPANY                    | EMERGENCY TELEPHONE NO.   |    |
|                     | Consumer Group - Industrial                     | (216) 566-2917            |    |
|                     | Cleveland, OH 44115                             |                           |    |
| DATE OF PREPARATION | 17-JUN-03                                       | INFORMATION TELEPHONE NO. |    |
|                     |   | (800) 247-3266            |    |

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

| % by WT | CAS No.    | INGREDIENT             | UNITS               | VAPOR PRESSURE |
|---------|------------|------------------------|---------------------|----------------|
| 15      | 74-98-6    | Propane                |                     |                |
|         |            | ACGIH TLV              | 2500 ppm            | 760 mm         |
|         |            | OSHA PEL               | 1000 ppm            |                |
| 7       | 106-97-8   | Butane                 |                     |                |
|         |            | ACGIH TLV              | 800 ppm             | 760 mm         |
|         |            | OSHA PEL               | 800 ppm             |                |
| 6       | 64742-89-8 | V. M. & P. Naphtha     |                     |                |
|         |            | ACGIH TLV              | 300 ppm             | 12 mm          |
|         |            | OSHA PEL               | 300 ppm             |                |
|         |            | OSHA PEL               | 400 ppm STEL        |                |
| 11      | 108-88-3   | Toluene                |                     |                |
|         |            | ACGIH TLV              | 50 ppm (skin)       | 22 mm          |
|         |            | OSHA PEL               | 100 ppm (skin)      |                |
|         |            | OSHA PEL               | 150 ppm (skin) STEL |                |
| 0.3     | 100-41-4   | Ethylbenzene           |                     |                |
|         |            | ACGIH TLV              | 100 ppm             | 7.1 mm         |
|         |            | ACGIH TLV              | 125 ppm STEL        |                |
|         |            | OSHA PEL               | 100 ppm             |                |
|         |            | OSHA PEL               | 125 ppm STEL        |                |
| 2       | 1330-20-7  | Xylene                 |                     |                |
|         |            | ACGIH TLV              | 100 ppm             | 5.9 mm         |
|         |            | ACGIH TLV              | 150 ppm STEL        |                |
|         |            | OSHA PEL               | 100 ppm             |                |
|         |            | OSHA PEL               | 150 ppm STEL        |                |
| 34      | 67-64-1    | Acetone                |                     |                |
|         |            | ACGIH TLV              | 500 ppm             | 180 mm         |
|         |            | ACGIH TLV              | 750 ppm STEL        |                |
|         |            | OSHA PEL               | 1000 ppm            |                |
| 4       | 108-10-1   | Methyl Isobutyl Ketone |                     |                |
|         |            | ACGIH TLV              | 50 ppm              | 16 mm          |
|         |            | ACGIH TLV              | 75 ppm STEL         |                |
|         |            | OSHA PEL               | 50 ppm              |                |
|         |            | OSHA PEL               | 75 ppm STEL         |                |

```

=====
0.5      1333-86-4  Carbon Black
                ACGIH TLV   3.5  mg/m3
                OSHA  PEL   3.5  mg/m3
=====

```

-----  
Section 3 -- HAZARDS IDENTIFICATION  
-----

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

-----  
Section 4 -- FIRST AID MEASURES  
-----

```

If INHALED:      If affected, remove from exposure.  Restore breathing.
                  Keep warm and quiet.
If on SKIN:      Wash affected area thoroughly with soap and water.
                  Remove contaminated clothing and launder before re-use.
If in EYES:      Flush eyes with large amounts of water for 15 minutes.
                  Get medical attention.
If SWALLOWED:    Do not induce vomiting.
                  Get medical attention immediately.
=====

```

-----  
Section 5 -- FIRE FIGHTING MEASURES  
-----

```

FLASH POINT                LEL      UEL
Propellant < 0 F          0.9      12.8
EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam
UNUSUAL FIRE AND EXPLOSION HAZARDS
Containers may explode when exposed to extreme heat.
Application to hot surfaces requires special precautions.
During emergency conditions overexposure to decomposition products may
cause a health hazard. Symptoms may not be immediately apparent. Obtain
medical attention.
SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus
should be used.
Water spray may be ineffective. If water is used, fog nozzles are
preferable. Water may be used to cool closed containers to prevent
pressure build-up and possible autoignition or explosion when exposed to
extreme heat.

```

=====  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
=====

## STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.  
Remove with inert absorbent.

=====  
Section 7 -- HANDLING AND STORAGE  
=====

## STORAGE CATEGORY

Not Available

## PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

=====  
Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION  
=====

## PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m<sup>3</sup> (total dust), 3 mg/m<sup>3</sup> (respirable fraction), OSHA PEL 15 mg/m<sup>3</sup> (total dust), 5 mg/m<sup>3</sup> (respirable fraction).

## VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits.

Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

## RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

## PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

## EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

## OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

=====  
Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES  
=====

PRODUCT WEIGHT 6.35 lb/gal 761 g/l  
SPECIFIC GRAVITY 0.76  
BOILING POINT <0 - 325 F <-18 - 162 C  
MELTING POINT Not Available  
VOLATILE VOLUME 87 %  
EVAPORATION RATE Faster than ether  
VAPOR DENSITY Heavier than air  
SOLUBILITY IN WATER N.A.  
pH 7.0  
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)  
Volatile Weight 47.00 % Less Water and Federally Exempt Solvents

=====  
Section 10 -- STABILITY AND REACTIVITY  
=====

STABILITY -- Stable  
CONDITIONS TO AVOID  
None known.  
INCOMPATIBILITY  
None known.  
HAZARDOUS DECOMPOSITION PRODUCTS  
By fire: Carbon Dioxide, Carbon Monoxide  
HAZARDOUS POLYMERIZATION  
Will not occur

=====  
Section 11 -- TOXICOLOGICAL INFORMATION  
=====

## CHRONIC HEALTH HAZARDS

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

=====  
TOXICOLOGY DATA  
=====

| CAS No.    | Ingredient Name        |      |     |     |               |       |
|------------|------------------------|------|-----|-----|---------------|-------|
| 74-98-6    | Propane                | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | Not Available |       |
| 106-97-8   | Butane                 | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | Not Available |       |
| 64742-89-8 | V. M. & P. Naphtha     | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | Not Available |       |
| 108-88-3   | Toluene                | LC50 | RAT | 4HR | 4000          | ppm   |
|            |                        | LD50 | RAT |     | 5000          | mg/kg |
| 100-41-4   | Ethylbenzene           | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | 3500          | mg/kg |
| 1330-20-7  | Xylene                 | LC50 | RAT | 4HR | 5000          | ppm   |
|            |                        | LD50 | RAT |     | 4300          | mg/kg |
| 67-64-1    | Acetone                | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | 5800          | mg/kg |
| 108-10-1   | Methyl Isobutyl Ketone | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | 2080          | mg/kg |
| 1333-86-4  | Carbon Black           | LC50 | RAT | 4HR | Not Available |       |
|            |                        | LD50 | RAT |     | Not Available |       |

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

=====  
 Section 15 -- REGULATORY INFORMATION  
 -----

## SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

| CAS No.   | CHEMICAL/COMPOUND      | % by WT | % Element |
|-----------|------------------------|---------|-----------|
| 108-88-3  | Toluene                | 11      |           |
| 100-41-4  | Ethylbenzene           | 0.3     |           |
| 1330-20-7 | Xylene                 | 2       |           |
| 108-10-1  | Methyl Isobutyl Ketone | 4       |           |

## CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.  
 TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

 =====  
 Section 16 -- OTHER INFORMATION  
 -----

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.