



Material Safety Data Sheet

The Martin Senour Co.
P.O. Box 6709
Cleveland, OH 44101

Emergency telephone number
Information telephone number
Date of preparation

(216) 566-2917
(216) 566-2902
January 1, 1998

©1998, The Martin Senour Co.

PRO LINE™ Professional Latex Interior Finishes (new numbering system)

L-PRO/MS2

		PREMIUM FLAT		PRO-LINE™ FLAT		PREMIUM EGGSHELL		PREMIUM SEMI-GLOSS		PRO-LINE™ SEMI-GLOSS																	
		71-1000 Bright White	71-1001 White White	71-1002 Midtone Base	71-1003 Deeptone Base	71-1011 Antique White	71-1040 Black	71-1185 Primer	72-1001 White White	72-1011 Antique White	72-1014 Acoustone White	72-1013 Mission White	72-1185 Primer/Sealer	71-2000 Bright White	71-2001 White White	71-2002 Midtone Base	71-2003 Deeptone Base	71-2011 Antique White	71-3000 Bright White	71-3001 White White	71-3002 Midtone Base	71-3003 Deeptone Base	71-3011 Antique White	72-3001 White White	72-3011 Antique White	72-3014 Acoustone White	72-3013 Mission White
— Section 2 — CAS No. Hazardous Ingredients (percent by weight)		ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)																						
112-34-5	§ 2-(2-Butoxyethoxy)-ethanol	Not Established			0.1																						
107-21-1	§ Ethylene Glycol.	C 50	50	PPM	0.1	less than 6% may be added due to tinting																					
64742-54-7	Heavy Paraffinic Oil.	5	5	Mg/M3	as Mist	1 in Deeptone Base only																					
14808-60-7	Quartz	0.1	0.1	Mg/M3	as Resp. Dust	0.1 - 13	0.2 - 7																				
14464-46-1	Cristobalite	0.05	0.05	Mg/M3	as Resp. Dust	0 - 3	3 - 4 except Primer/Sealer	0 - 0.1	0 - 0.1	0.1 except Mission White																	
1332-58-7	Kaolin	2	5	Mg/M3	as Resp. Dust	0 - 10	3 - 18																				
14807-96-6	Talc	2	2	Mg/M3	as Resp. Dust	0 - 4	4 in Acoustone White only																				
12001-26-2	Mica	3	3	Mg/M3	as Resp. Dust	3 in Bright White only																					
471-34-1	Calcium Carbonate.	10	15[5]	Mg/M3	as Dust [Resp. Fraction]	0 - 15	5 in Acoustone White only	9 - 19	0 - 6	3 - 4 except Acoustone White																	
13463-67-7	Titanium Dioxide.	10	10[5]	Mg/M3	as Dust [Resp. Fraction]	5 - 15 except Black	3 - 8	7 - 23	9 - 27	12 - 16																	
1333-86-4	Carbon Black.	3.5	3.5	Mg/M3		0 - 2		0 - 1	0 - 1																		
Weight per Gallon (lbs.)						9.6 - 12.2	9.4 - 11.3	10.3 - 11.5	9.6 - 11.0	9.6 - 9.7																	
Percent Water						40.2 - 69.2	46.3 - 70.8	38.0 - 54.0	40.3 - 59.8	57.4 - 63.7																	
VOC (Volatile Organic Compounds) Total - lbs./gal.						0.1 - 0.4	0.1 - 0.4	0.3 - 0.6	0.2 - 0.6	0.1 - 0.3																	
VOC Less Water & Federally Exempt Solvents - lbs./gal.						0.4 - 1.1	0.4 - 1.0	1.0 - 1.2	0.7 - 1.3	0.3 - 1.1																	
Flash Point (°F) / HMIS (NFPA) Rating (health - flammability - reactivity)						None / 2* - 0 - 0	None / 2* - 0 - 0	None / 2* - 0 - 0	None / 2* - 0 - 0	None / 2* - 0 - 0																	

P
E
R
C
E
N
T

B
Y

W
E
I
G
H
T

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

Section 3 — Physical Data

<i>PRODUCT WEIGHT</i>	See TABLE	<i>EVAPORATION RATE</i>	Slower than Ether
<i>SPECIFIC GRAVITY</i>	1.13-1.79	<i>VAPOR DENSITY</i>	Heavier than Air
<i>BOILING RANGE</i>	212-477 °F	<i>MELTING POINT</i>	N.A.
<i>VOLATILE VOLUME</i>	45-82 %	<i>SOLUBILITY IN WATER</i>	N.A.
<i>pH</i>	9.0-9.5	<i>PHOTOCHEMICALLY REACTIVE</i>	No

Section 4 — Fire and Explosion Hazard Data

FLAMMABILITY CLASSIFICATION Not Applicable *FLASH POINT* See TABLE *LEL* N.A. *UEL* N.A.

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 5 — Health Hazard Data

ROUTES OF EXPOSURE

Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

ACUTE Health Hazards

EFFECTS OF OVEREXPOSURE

Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

EMERGENCY AND FIRST AID PROCEDURES

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Get medical attention.

CHRONIC Health Hazards

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

Section 6 — Reactivity Data

STABILITY - Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Metals in Section 2

HAZARDOUS POLYMERIZATION - Will Not Occur

Section 7 — Spill Or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD

Waste from 728-8513 and 728-8521 Wood Primer may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for extractability to determine the applicable EPA hazardous waste numbers.

Waste from other products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section 8 — Protection Information

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), 3 mg./m3 (respirable fraction), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding, wirebrushing, abrading, burning or welding the dried film, wear a particulate respirator approved by NIOSH/MSHA for protection against non-volatile materials in Section II.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 — Precautions

DOL STORAGE CATEGORY - Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 10 — Other Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: These products, except for 60-1001, 60-1002, 60-1003, 60-2000, 60-2001, 60-2002, 60-2003, 61-2002, 61-2003, 71-3011, 728-8228, 61-1191, and 61-1003 contain chemicals known to the State of California to cause cancer.

60-1001, 60-1002, 60-1003, 60-2000, 60-2001, 60-2002, 60-2003, 61-2002, 61-2003, 71-3011, 728-8228, 61-1191, and 61-1003 contain a chemical known to the State of California to cause cancer.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.