



# QUEST

INDUSTRIAL PRODUCTS

## MATERIAL SAFETY DATA SHEET

Issued to . . . . . : Midwest Products Co., Inc.

400 S. Indiana Street

Hobart

IN 46342

Attention: . . . . . : Material Safety Data Sheet Coordinator

The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product.

We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.

You are required to keep this MSDS on file for reference by company employees or government regulatory officials.

If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.



# QUEST

INDUSTRIAL PRODUCTS

## MATERIAL SAFETY DATA SHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 01583 100054 1B  
PRODUCT NAME . . . : Clear 65-1  
PRODUCT CLASS . . . : Touch-Up Bottle

MSDS PREPARATION DATE : 03/28/2014

MANUFACTURER IDENTIFICATION:

QUEST INDUSTRIAL PRODUCTS  
PO BOX 1090  
MENOMONEE FALLS WI 53052-1090

CUSTOMER IDENTIFICATION:

Midwest Products Co., Inc.  
400 S. Indiana Street  
Hobart IN 46342

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300  
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887  
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ACRYLIC POLYMER

CAS# 96591-17-2

ACRYLIC POLYMER

PCT BY WT: 3.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA NO INFO  
ACGIH TLV-STEL NO INFO  
LD50(ORAL) 5000 mg/kg  
LD50(DERMAL) 2000 mg/kg  
LC50 20000 mg/m3

2 ETHYL ACETATE

CAS# 141-78-6

ETHYL ACETATE

PCT BY WT: 3.0000 VAPOR PRESSURE: 76.000 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 400 ppm  
COMPANY N.E.  
LD50(ORAL) 4935 mg/kg (Rabbit)  
LD50(DERMAL) 17962 mg/kg (Rabbit)  
LC50 45000 mg/m3 (Mouse)

3 NITROCELLULOSE

CAS# 9004-70-0

NITROCELLULOSE

QUEST INDUSTRIAL PRODUCTS



# QUEST

INDUSTRIAL PRODUCTS

PAGE 3

## MATERIAL SAFETY DATA SHEET

01583 100054 1B

---

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

---

PCT BY WT: 4.0000 LEL 100.00

EXPOSURE LIMIT:

ACGIH TLV-TWA NOT EST.

ACGIH TLV-STEL NOT EST.

---

4 DIACETONE ALCOHOL

CAS# 123-42-2

DIACETONE ALCOHOL

PCT BY WT: 4.0000 VAPOR PRESSURE: 1.000 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 50 ppm

ACGIH TLV-STEL NO INFO

OSHA PEL-TWA 50 ppm

COMPANY N.E.

---

5 METHYL ETHYL KETONE

CAS# 78-93-3

METHYL ETHYL KETONE

PCT BY WT: 14.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 200 ppm

ACGIH TLV-STEL 300 ppm

OSHA PEL-TWA 200 ppm

COMPANY N.E.

LD50(ORAL) 2737 mg/kg (rat)

LD50(DERMAL) 6480 mg/kg (rat)

LC50 23500 mg/m3 (rat)

OTHER LIMITS:

EINECS 201-159-0

---

6 GLYCOL ETHER PM ACETATE

CAS# 108-65-6

PROPYLENE GLYCOL METHYL ETHER ACETATE

PCT BY WT: 5.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA NOT ESTABLISHED

ACGIH TLV-STEL NOT ESTABLISHED

LD50(ORAL) 8500 mg/kg (rat)

LD50(DERMAL) 5000 mg/kg (rat)

LC50 5321 mg/m3 (rat)

OTHER LIMITS:

EINECS 203-603-9

---



# QUEST

INDUSTRIAL PRODUCTS

PAGE 4

## MATERIAL SAFETY DATA SHEET

7 TOLUENE

CAS# 108-88-3

TOLUENE

PCT BY WT: 30.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40

EXPOSURE LIMIT:

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

ACGIH TLV-TWA 20 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 50 ppm  
COMPANY N.E.  
LD50(ORAL) 636 mg/kg (rat)  
LD50(DERMAL) 14124 mg/kg (rabbit)  
LC50 7523 mg/m3 (mouse)

OTHER LIMITS:

Prop 65-Developmental-01/01/91 EINECS 203-625-9

8 ISOBUTYL ACETATE

CAS# 110-19-0

ISOBUTYL ACETATE

PCT BY WT: 25.0000 LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA 150 ppm  
ACGIH TLV-STEL NO INFO  
OSHA PEL-TWA 150 ppm  
COMPANY N.E.  
LD50(ORAL) 13400 mg/kg (Rat)  
LD50(DERMAL) >17400 mg/kg (Rabbit)  
LC50 >8000 ppm (Rat)

9 ISOPROPYL ALCOHOL

CAS# 67-63-0

ISOPROPANOL

PCT BY WT: 2.0000 LEL 2.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm  
ACGIH TLV-STEL 500 ppm  
OSHA PEL-TWA 400 ppm  
COMPANY N.E.

10 ISOBUTYL ALCOHOL

CAS# 78-83-1

ISOBUTYL ALCOHOL

PCT BY WT: 5.0000 LEL 1.70

EXPOSURE LIMIT:



# QUEST

## INDUSTRIAL PRODUCTS

# MATERIAL SAFETY DATA SHEET

ACGIH TLV-TWA	50 ppm
ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	50 ppm
COMPANY	N.E.

OTHER LIMITS:

EINECS 201-148-0

-----  
 \*\*\*\*\*  
 This substance is classified as a hazardous air pollutant.  
 -----

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

-----  
 \*\*\*\*\*  
 This product contains no reported carcinogens or suspected  
 carcinogens.  
 -----

### SECTION 3 - HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW:

- Harmful if inhaled.
- Causes eye irritation.
- Causes skin irritation.
- Vapors irritating to eyes and respiratory tract.
- Flammable liquid and vapor.

#### EYE:

May cause severe corneal injury if liquid comes in contact with the eyes.

#### SKIN:

- May cause skin irritation.
- Prolonged contact with the skin can cause chemical burns.
- Harmful if absorbed through the skin.
- Skin contact may aggravate an existing dermatitis.

#### INHALATION:

- Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
- Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
- Excessive inhalation of vapors can cause nasal and respiratory irritation.
- Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.
- Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to material(s) in this product.
- Persons with pre-existing, non-specific bronchial hyperreactivity can respond to concentrations below the TLV with symptoms as well as an asthma attack.



# QUEST

INDUSTRIAL PRODUCTS

PAGE 6

## MATERIAL SAFETY DATA SHEET

### INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

May cause nausea, vomiting and diarrhea.

### CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Lung damage
- Liver damage
- Spleen damage

---

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

---

Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

Liver damage

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

---

### SECTION 4 - FIRST AID MEASURES

---

#### EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

#### SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

#### INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

#### INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials



# QUEST

INDUSTRIAL PRODUCTS

## MATERIAL SAFETY DATA SHEET

ingested.

---

### SECTION 5 - FIRE FIGHTING MEASURES

---

#### FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Explosion Level . . . . . : Low (LEL) - 1.3  
High (UEL)- 444.0

#### EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

#### FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Flashpoint . . . . . : 24.0 °F

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.

Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

---

### QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

---

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

---

#### CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.

Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

---

### SECTION 7 - HANDLING AND STORAGE

---

#### HANDLING:

Wash hands thoroughly after handling.

#### STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

---

### SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

---

#### ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

#### RESPIRATORY PROTECTION:



# QUEST

## INDUSTRIAL PRODUCTS

# MATERIAL SAFETY DATA SHEET

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

**SKIN PROTECTION:**

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

**EYE PROTECTION:**

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

**OTHER PROTECTIVE EQUIPMENT:**

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

**HYGIENIC PRACTICES:**

Wash hands before eating or smoking. Smoke in designated areas only.

-----  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
-----

Vapor Pressure . . . . . : 85.00 mm Hg @ 20 C  
Vapor Density . . . . . : 6.70  
Boiling Range . . . . . : Lower - 77.0 °F  
-----

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B  
-----

Higher - 543.0 °F  
Specific Gravity . . . . . : .895  
Formula Weight per Volume . . . . . : 7.4510 LB/GL  
VOC (Calculated, LB/GAL) . . . . . : 6.687  
VOC (Calculated, GM/L). . . . . : 801.30  
Percent Volatile by Weight. . . . . : 88.7880  
Percent Volatile by Volume . . . . . : 92.2326  
Evaporation Rate . . . . . : 6.000 (n-Butyl Acetate = 1)  
Viscosity . . . . . : -N/A  
-----

SECTION 10 - STABILITY AND REACTIVITY  
-----

**CONDITIONS TO AVOID:**

Avoid contact with heat, sparks, and open flame.

**INCOMPATIBILITIES:**

Strong oxidizing agents.

**DECOMPOSITION:**

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

**POLYMERIZATION:**

No hazardous polymerization will occur under normal conditions.

**STABILITY:**

The product is stable under normal storage conditions.  
-----





# QUEST

INDUSTRIAL PRODUCTS

PAGE 9

## MATERIAL SAFETY DATA SHEET

### SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

### SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

### SECTION 13 - DISPOSAL CONSIDERATIONS

#### WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

### SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

### QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

### SECTION 15 - REGULATORY INFORMATION

#### SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

dimethyl 1,2-benzenedicarboxylate

CAS# 131-11-3 PCT BY WT: 4.1220

#### TOLUENE

CAS# 108-88-3 PCT BY WT: 29.7330



# QUEST

INDUSTRIAL PRODUCTS

## MATERIAL SAFETY DATA SHEET

ISOPROPANOL

CAS# 67-63-0 PCT BY WT: 2.0000

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

-----	CHEMICAL NAME	-----	CAS NUMBER
-------	---------------	-------	------------

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the

QUEST INDUSTRIAL PRODUCTS

01583 100054 1B

Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH:            FLAMMABILITY:            REACTIVITY:            PERSONAL PROTECTION: