
SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : 01583 658530 3.5
PRODUCT NAME . . . : CLEAR BRUSHING AEROFLAT 40-4
PRODUCT CLASS . . . : Glass Bottles

MSDS PREPARATION DATE : 08/10/2012

MANUFACTURER IDENTIFICATION:

RAABE COMPANY
PO BOX 1090

MENOMONEE FALLS

WI 53052-1090

CUSTOMER IDENTIFICATION:

Midwest Products Co., Inc.
400 S. Indiana Street

Hobart

IN 46342

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ACRYLIC POLYMER

CAS# 96591-17-2

ACRYLIC POLYMER

PCT BY WT: 3.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA	NO INFO
ACGIH TLV-STEL	NO INFO
LD50 (ORAL)	5000 mg/kg
LD50 (DERMAL)	2000 mg/kg
LC50	20000 mg/m3

2 ETHYL ACETATE

CAS# 141-78-6

ETHYL ACETATE

PCT BY WT: 3.0000 VAPOR PRESSURE: 76.000 MMHG @ 68F LEL 2.20

EXPOSURE LIMIT:

ACGIH TLV-TWA	400 ppm
ACGIH TLV-STEL	NO INFO
OSHA PEL-TWA	400 ppm
COMPANY	N.E.
LD50 (ORAL)	4935 mg/kg (Rabbit)
LD50 (DERMAL)	17962 mg/kg (Rabbit)
LC50	45000 mg/m3 (Mouse)

3 NITROCELLULOSE

CAS# 9004-70-0

NITROCELLULOSE

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

 PCT BY WT: 4.0000 LEL 100.00
 EXPOSURE LIMIT:
 ACGIH TLV-TWA NOT EST.
 ACGIH TLV-STEL NOT EST.

4 AMORPHOUS PRECIPITATED SILICA
 CAS# 112926-00-8
 AMORPHOUS PRECIPITATED SILICA
 PCT BY WT: 2.0000
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 10 mg/m3
 ACGIH TLV-STEL NO INFO
 LD50 (ORAL) >10000 mg/kg (rat)
 LD50 (DERMAL) NO INFORMATION
 LC50 >139 mg/m3 (rat)
 OTHER LIMITS:

EINECS NONE

 5 DIACETONE ALCOHOL
 CAS# 123-42-2
 DIACETONE ALCOHOL
 PCT BY WT: 3.0000 VAPOR PRESSURE: 1.000 MMHG @ 68F LEL 1.80
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 50 ppm
 ACGIH TLV-STEL NO INFO
 OSHA PEL-TWA 50 ppm
 COMPANY N.E.

6 METHYL ETHYL KETONE
 CAS# 78-93-3
 METHYL ETHYL KETONE
 PCT BY WT: 20.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 200 ppm
 ACGIH TLV-STEL 300 ppm
 OSHA PEL-TWA 200 ppm
 COMPANY N.E.
 LD50 (ORAL) 2737 mg/kg (rat)
 LD50 (DERMAL) 6480 mg/kg (rat)
 LC50 23500 mg/m3 (rat)
 OTHER LIMITS:

EINECS 201-159-0

 7 GLYCOL ETHER PM ACETATE
 CAS# 108-65-6
 PROPYLENE GLYCOL METHYL ETHER ACETATE
 PCT BY WT: 4.0000 VAPOR PRESSURE: 3.700 MMHG @ 68F LEL 1.30
 EXPOSURE LIMIT:

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

ACGIH TLV-TWA NOT ESTABLISHED
ACGIH TLV-STEL NOT ESTABLISHED
LD50 (ORAL) 8500 mg/kg (rat)
LD50 (DERMAL) 5000 mg/kg (rat)
LC50 5321 mg/m3 (rat)

OTHER LIMITS:

EINECS 203-603-9

8 TOLUENE

CAS# 108-88-3

TOLUENE

PCT BY WT: 24.0000 VAPOR PRESSURE: 38.000 MMHG @ 68F LEL 1.40

EXPOSURE LIMIT:

ACGIH TLV-TWA 20 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 50 ppm
COMPANY N.E.
LD50 (ORAL) 636 mg/kg (rat)
LD50 (DERMAL) 14124 mg/kg (rabbit)
LC50 7523 mg/m3 (mouse)

OTHER LIMITS:

Prop 65-Developmental-01/01/91 EINECS 203-625-9

9 ISOBUTYL ACETATE

CAS# 110-19-0

ISOBUTYL ACETATE

PCT BY WT: 18.0000 LEL 1.30

EXPOSURE LIMIT:

ACGIH TLV-TWA 150 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 150 ppm
COMPANY N.E.
LD50 (ORAL) 13400 mg/kg (Rat)
LD50 (DERMAL) >17400 mg/kg (Rabbit)
LC50 >8000 ppm (Rat)

10 ISOPROPYL ALCOHOL

CAS# 67-63-0

ISOPROPANOL

PCT BY WT: 10.0000 LEL 2.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 400 ppm
ACGIH TLV-STEL 500 ppm
OSHA PEL-TWA 400 ppm
COMPANY N.E.

11 ISOBUTYL ALCOHOL

CAS# 78-83-1

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

ISOBUTYL ALCOHOL
PCT BY WT: 4.0000 LEL 1.70
EXPOSURE LIMIT:
ACGIH TLV-TWA 50 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 50 ppm
COMPANY N.E.
OTHER LIMITS: EINECS 201-148-0

This substance is classified as a hazardous air pollutant.

This product contains no reported carcinogens or suspected
carcinogens.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled.
Causes eye irritation.
Causes skin irritation.
Vapors irritating to eyes and respiratory tract.
Flammable liquid and vapor.

EYE:
May cause severe corneal injury if liquid comes in contact with the eyes.

SKIN:
May cause skin irritation.
Prolonged contact with the skin can cause chemical burns.
Harmful if absorbed through the skin.
Skin contact may aggravate an existing dermatitis.

INHALATION:
Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.
Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.
Excessive inhalation of vapors can cause nasal and respiratory irritation.
Prolonged inhalation of dusts containing free silica may result in the development of a disabling pulmonary fibrosis(lung disease) known as silicosis.
Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.
Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to material(s) is this product.

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

Persons with pre-existing, non-specific bronchial hyperreactivity can respond to concentrations below the TLV with symptoms as well as an asthma attack.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

May cause nausea, vomiting and diarrhea.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

- Kidney damage
- Lung damage
- Liver damage
- Spleen damage
- Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

- Liver damage

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting or not must be made by a physician after careful consideration of all materials ingested.

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint : 24.0 °F
Explosion Level : Low (LEL) - 1.3
High (UEL) - 444.0

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used.
Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire.
Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.
Keep away from heat, sparks and flame.
Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component (see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	:	85.00	mm Hg @ 20 C
Vapor Density	:	6.70	
Boiling Range	:	Lower - 77.0 °F	
		Higher - 543.0 °F	
Specific Gravity	:	.896	
Formula Weight per Volume	:	7.4561	LB/GL
VOC (Calculated, LB/GAL)	:	6.385	
VOC (Calculated, GM/L)	:	765.11	
Percent Volatile by Weight	:	85.4957	
Percent Volatile by Volume	:	90.2410	
Evaporation Rate	:	6.000	(n-Butyl Acetate = 1)
Viscosity	:	-N/A	

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

dimethyl 1,2-benzenedicarboxylate

CAS# 131-11-3 PCT BY WT: 5.5890

TOLUENE

CAS# 108-88-3 PCT BY WT: 24.1560

ISOPROPANOL

CAS# 67-63-0 PCT BY WT: 9.5430

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

RAABE COMPANY
MATERIAL SAFETY DATA SHEET

01583 658530 3.5

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

----- CHEMICAL NAME ----- CAS NUMBER

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3 %

----- CHEMICAL NAME ----- CAS NUMBER

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 3 REACTIVITY: 0 PERSONAL PROTECTION: G