

9724860

36310

MATERIAL SAFETY DATA SHEET

NASCO ARTIST ACRYLIC GEL MEDIUM
TRAVEL NAME ON LABEL

ROCK PAINT DISTRIBUTING CORP.

MANUFACTURER

MSDS NUMBER

365 SUNNYSIDE DR. P.O. BOX 482

ADDRESS

CAS NUMBER

MILTON, WI 53563

JUNE 2006

DATE PREPARED

(608)868-6873 (920) 563-8545

PHONE NUMBER(FOR INFORMATION)

PREPARED BY

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS: CHEMICAL NAME & COMMON NAMES	%	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED
WATER				
ACRYLIC EMULSION				
CALCIUM CARBONATE				
PROPYLENE GLYCOL				
CELLULOSIC				

AS PER ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI) INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT - ABOUT 212	SPECIFIC GRAVITY (H2O=1) - ABOUT 9LBS PER GAL
VAPOR PRESSURE (mm Hg & TEMPERATURE) - 17mm Hg	MELTING POINT - N/A
VAPOR DENSITY (AIR=1) - NOT AVAILABLE	EVAPORATION RATE (WATER=1) - SLOWER
SOLUBILITY IN WATER - DILUTABLE	WATER REACTIVE - N/A
APPEARANCE & ODOR - SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT & METHOD USED N/A	AUTO IGNITION TEMPERATURE N/A	FLAMMABILITY LIMITS IN AIR % BY VOLUME N/A
EXTINGUISHER MEDIA FOAM - DRY CHEMICAL - CO2 - WATER SPRAY OR FOG	LEL	UEL
SPECIAL FIRE FIGHTING PROCEDURES N/A		
UNUSUAL FIRE AND EXPLOSION HAZARDS N/A		

SECTION 4 - REACTIVITY HAZARD DATA

ARTIST GEL -2

STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE	CONDITIONS TO AVOID NONE KNOWN
INCOMPATIBILITY (MATERIALS TO AVOID) NONE KNOWN-HOWEVER PRODUCT PROPERTIES MAY BE ALTERED BY MIXING WITH SOME MATERIALS.	
HAZARDOUS DECOMPOSITION PRODUCTS THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE AND TRACES OF MONOMER.	
HAZARDOUS POLYMERIZATION <input type="checkbox"/> MAY OCCUR <input checked="" type="checkbox"/> WILL NOT OCCUR	CONDITIONS TO AVOID

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY <input type="checkbox"/> INHALATION <input type="checkbox"/> SKIN ABSORPTION	<input type="checkbox"/> INGESTION	CARCINOGEN LISTED IN <input type="checkbox"/> IARC MONOGRAPH	<input type="checkbox"/> NTP <input type="checkbox"/> OSHA <input type="checkbox"/> NOT LISTED
HEALTH HAZARDS AGUTE CHRONIC		<input checked="" type="checkbox"/> NOT HAZARDOUS	
SIGNS AND SYMPTOMS			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE			
EMERGENCY FIRST AID PROCEDURES -			
SEEK MEDICAL ASSISTANCE FOR FURTHER TREATMENT, OBSERVATION AND SUPPORT IS NECESSARY.			
EYE CONTACT - DIRECT CONTACT WITH EMULSION MAY RESULT IN IRRITATION. FLUSH EYES IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND CONSULT A PHYSICIAN. REMOVE CONTACTS FROM VICTIM.			
SKIN CONTACT - PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION, WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE.			
INHALATION - N/A			
INGESTION - IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.			

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE) -			
PROTECTIVE GLOVES - RUBBER GLOVES RECOMMENDED	EYE PROTECTION - CHEMICAL GOGGLES WITH EYE GUARD		
VENTILATION TO BE USED - LOCAL EXHAUSE OTHER (SPECIFY) -	MECHANICAL (GENERAL) -	SPECIAL -	
OTHER PROTECTIVE CLOTHING AND EQUIPMENT - N/A			
HYGIENIC WORK PRACTICES -			

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE/LEAK PROCEDURES

STEPS TO BE TAKEN IS MATERIAL IS SPILLED OR RELEASED - ABSORB WITH DRYING MATERIAL OR FLUSH SPILLED MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINER. PREVENT SPILLED LIQUID FROM ENTERING SEWERS, STORM DRAINS, DRAINAGE SYSTEMS AND NATURAL WATERWAYS.
WASTE DISPOSAL METHODS - DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE SHOULD BE STORED AT ROOM TEMPERATURE TO PROLONG SHELF LIFE. KEEP FROM FREEZING AND FROM EXCESSIVE HEAT.
OTHER PRECAUTIONS AND/OR SPECIAL HAZARDS - N/A

HIMS RATING HEALTH _____ FLAMMABILITY _____ REACTIVITY _____ PERSONAL PROTECTION _____