

**FOR CHEMICAL EMERGENCY**  
**Call INFOTRAC**  
**1-800-535-5053**  
**24 Hrs. per day, 7 days per week**

## MATERIAL SAFETY DATA SHEET

ABBREVIATIONS: NA = NOT APPLICABLE HEALTH = 2  
 ND = NOT DETERMINED FLAMMABILITY = 3  
 NE = NOT ESTABLISHED REACTIVITY = 1  
 PERSONAL PROTECTION = G

### SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME: QUIK STRIPE ARCTIC WHITE

PRODUCT TYPE: AEROSOL

PIONEER MANUFACTURING COMPANY  
 4529 INDUSTRIAL PARKWAY  
 CLEVELAND, OHIO 44135  
 TELEPHONE: 800-877-1500

EMERGENCY TELEPHONE (800) 535-5053  
 INFOTRAC

DATE PREPARED: 4/15/2003

PREPARED BY: GSS

D.O.T. SHIPPING NAME ORMD - CONSUMER COMMODITY

### SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME:	CAS NO.	OSHA PEL	ACGIH TLV	% WT
ALIPHATIC HYDROCARBON	64742-89-8	500 ppm	100 ppm	20
ACETONE	67-64-1	750 ppm	750 ppm	10
MINERAL SPIRITS	8052-41-3	100 ppm	100 ppm	
CALCIUM CARBONATE	1317-65-3	NE	10 mg/M3	10
TOLUENE *	108-88-3	100 ppm	50 ppm	5
PROPANE/BUTANE BLEND	68476-86-8	ND	ND	15

\* SUBJECT TO REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313, 40 CFR 372

WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

### SECTION 3 - PHYSICAL DATA

BOILING POINT (° F) NA. SPECIFIC GRAVITY: 1.25 (PAINT)  
 VAPOR PRESSURE: NE MELTING POINT: NA  
 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE (BUAC=1): SLOWER THAN BUAC  
 SOLUBILITY IN WATER: INSOLUBLE pH: NA  
 APPEARANCE/ODOR: WHITE LIQUID, MILD SOLVENT ODOR

### SECTION 4 - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): -10 F T.O.C.

FLAMMABILITY LIMITS: LEL 1.1 UEL 12.8

EXTINGUISHING MEDIA: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL.

SPECIAL FIRE FIGHTING PROCEDURES: EXPOSURE TO HEAT MAY CAUSE BURSTING OF AEROSOL CANS.

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: WATER STREAMS WOULD SPREAD FIRE. STATIC ELECTRICITY COULD CAUSE IGNITION.

