

# valspar

## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identification** *Plasti-Kote Rust Not Enamel*  
**Product ID:** 400.0000360.076  
**Product Name:** 360 FLAT BLACK 6U  
**Product Use:** Paint product.  
**Print date:** 27/Jun/2009  
**Revision Date:** 26/Jun/2009

#### Company Identification

The Valspar Corporation - Architectural Coatings Division  
1000 Lake Road  
Medina, OH 44256

**Manufacturer's Phone:** 1-330-725-4511

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Eye Contact:

- Severe eye irritation

#### Skin Contact:

- Dermatitis
- Causes skin irritation.
- May cause defatting of the skin.

#### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Harmful if swallowed.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

#### Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- Asphyxia

#### Acute Other Health Effects:

- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause frostbite

**Target Organ and Other Health Effects:**

- Cardiac arrhythmias
- Liver injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.
- Kidney injury may occur.
- Blood disorders

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Carcinogens:**

- Possible cancer hazard. Contains material which may cause cancer based on animal data.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	Acetone
PROPANE 74-98-6	15 - 20	Propane
METHYL ISOBUTYL KETONE 108-10-1	10 - 15	Methylisobutyl ketone
BUTANE 106-97-8	5 - 10	Butane
BUTYL ACETATE 123-86-4	5 - 10	n-Butyl acetate
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	Ethyl 3-ethoxypropionate
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	Carbon black

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. If medical assistance is not immediately available, flush an additional 15 minutes. Get medical attention immediately.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Do not give direct mouth-to-mouth resuscitation if inhaled. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

**5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	-31°F (-35°C)
Lower explosive limit:	1 %
Upper explosive limit:	13 %
Autoignition temperature:	not determined -°F (°C)
Sensitivity to impact:	no
Sensitivity to static discharge:	Subject to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

None known.

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment****Eye and face protection:**

Chemical goggles, also wear a face shield if splashing hazard exists.

**Skin protection:**

Appropriate chemical resistant gloves should be worn.

**Other Personnel Protection Data:**

To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

**Exposure Guidelines**

**OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	2400 mg/m <sup>3</sup> 1000 ppm		
PROPANE 74-98-6	15 - 20	1800 mg/m <sup>3</sup> 1000 ppm		
METHYL ISOBUTYL KETONE 108-10-1	10 - 15	410 mg/m <sup>3</sup> 100 ppm		
BUTYL ACETATE 123-86-4	5 - 10	710 mg/m <sup>3</sup> 150 ppm		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup>		

**ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	500 ppm	750 ppm		
PROPANE 74-98-6	15 - 20	1000 ppm			
METHYL ISOBUTYL KETONE 108-10-1	10 - 15	50 ppm	75 ppm		
BUTANE 106-97-8	5 - 10	1000 ppm			
BUTYL ACETATE 123-86-4	5 - 10	150 ppm	200 ppm		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup>			

**9. PHYSICAL PROPERTIES**

Odor:

Normal for this product type.

## 9. PHYSICAL PROPERTIES

Physical State:	Aerosol
pH:	not determined
Vapor pressure:	NOT DETERMINED mmHg @ 68°F (20°C)
Vapor density (air = 1.0):	5.0
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	6.3
Specific Gravity:	.76
Evaporation rate (butyl acetate = 1.0):	5.6
Flash point (Fahrenheit):	-31°F (-35°C)
Lower explosive limit:	1 %
Upper explosive limit:	13 %
Autoignition temperature:	not determined -°F (°C)

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.

**Sensitivity to static discharge:** Subject to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40	Inhalation LC50 Rat : 50100 mg/m <sup>3</sup> /8H Inhalation LC50 Mouse : 44 gm/m <sup>3</sup> /4H Oral LD50 Rat : 5800 mg/kg Oral LD50 Mouse : 3 gm/kg
METHYL ISOBUTYL KETONE 108-10-1	10 - 15	Inhalation LC50 Mouse : 23300 mg/m <sup>3</sup> Oral LD50 Rat : 2080 mg/kg Oral LD50 Mouse : 2671 mg/kg Dermal LD50 Rabbit : >20 mL/kg
BUTANE 106-97-8	5 - 10	Inhalation LC50 Rat : 658 gm/m <sup>3</sup> /4H Inhalation LC50 Mouse : 680 gm/m <sup>3</sup> /2H
BUTYL ACETATE 123-86-4	5 - 10	Inhalation LC50 Rat : 2000 ppm/4H Inhalation LC50 Mouse : 6 gm/m <sup>3</sup> /2H Oral LD50 Rat : 10768 mg/kg Oral LD50 Mouse : 6 gm/kg Dermal LD50 Rabbit : >17600 mg/kg
ETHYL 3- ETHOXYPROPIONATE 763-69-9	1 - 5	Oral LD50 Rat : 5 gm/kg Dermal LD50 Rabbit : 10 mL/kg
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	ORAL LD50 (RAT): >10,000 MG/KG, INTRAVAVENOUS LD50 (RAT): 120 MG/KG

### Mutagens/Teratogens/Carcinogens:

Possible cancer hazard. Contains material which may cause cancer based on animal data.

IARC has classified carbon black as possibly carcinogenic to humans (Group 2B).

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1			Monograph 65, 1996

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: CONSUMER COMMODITY ORM-D  
UN ID Number: CONCOM

### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

#### International Air Transport Association (IATA):

Proper Shipping Name: AEROSOLS, FLAMMABLE  
Hazard Class: 2.1  
UN ID Number: UN1950

#### International Maritime Organization (IMO):

Proper Shipping Name: AEROSOLS  
Hazard Class: 2.1  
IMO UN/ID Number: UN1950

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
DIMETHYL KETONE- EXEMPT SOLVENT 67-64-1	35 - 40			5000
METHYL ISOBUTYL KETONE 108-10-1	10 - 15		form R reporting required for 1.0% de minimis concentration	5000
BUTYL ACETATE 123-86-4	5 - 10			5000

### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: yes  
Reactivity: no

Sudden Pressure: yes

## U.S. STATE REGULATIONS:

### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

### Pennsylvania Right To Know:

DIMETHYL KETONE- EXEMPT SOLVENT	67-64-1
BUTYL ACETATE	123-86-4
ETHYL 3-ETHOXYPROPIONATE	763-69-9
METHYL ISOBUTYL KETONE	108-10-1
BUTANE	106-97-8
PROPANE	74-98-6

### Additional Non-Hazardous Materials

PROPRIETARY RESIN	Trade Secret
-------------------	--------------

### Rule 66 status of product

Not photochemically reactive.

## INTERNATIONAL REGULATIONS - Chemical Inventories

### US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

### Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

## 16. OTHER INFORMATION

### HMIS Codes

Health:	2*
Flammability:	4
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By:

Regulatory Affairs Department

Print date:

27/Jun/2009

Revision Date:

26/Jun/2009