



# Material Safety Data Sheet

The Sherwin-Williams Co.  
101 Prospect Ave. N.W.  
Cleveland, OH 44115

Emergency telephone number  
Information telephone number  
Date of preparation

(216) 566-2917  
(216) 566-2902  
June 14, 2002

©2002, The Sherwin-Williams Co.

## DTM Acrylic Enamel, Semi-Gloss

## B66/2

| CAS No.     | — Section 2 —<br>Hazardous Ingredients<br>(percent by weight) | ACGIH         | OSHA          | Units                             | LD50                | LC50              | Vapor          | B66W200                           | B66W211        | B66W213      | B66T204           | B66A50            | B66W1           | B71Y1          |
|-------------|---|---------------|---------------|-----------------------------------|---------------------|-------------------|----------------|-----------------------------------|----------------|--------------|-------------------|-------------------|-----------------|----------------|
|             |   | TLV<br><STEL> | PEL<br><STEL> |                                   | (Rat-Oral)<br>mg/kg | (Rat)<br>ppm/4hr. | Pressure<br>mm | Ultra<br>White                    | Extra<br>White | Deep<br>Base | Ultradeep<br>Base | Bonding<br>Primer | Primer<br>White | Wash<br>Primer |
| 111-77-3    | § 2-(2-Methoxyethoxy)-ethanol                                 | NAv           | NAv           |                                   | 5500                | NAv               | 1.0            | 3                                 | 4              | 4            | 3                 |                   |                 |                |
| 111-76-2    | § 2-Butoxyethanol   | 20            | 20            | ppm (skin)                        | 470                 | NAv               | 0.9            |                                   |                |              |                   |                   |                 | 2              |
| 112-34-5    | § 2-(2-Butoxyethoxy)-ethanol                                  | NAv           | NAv           |                                   | 5660                | NAv               | 0.1            | 1                                 |                |              | 3                 |                   | 1               |                |
| 107-21-1    | § Ethylene Glycol.  | C 50          | C 50          | ppm                               | 4700                | NAv               | 0.1            | 2 - 4                             | 0 - 2          | 0 - 2        | 1 - 3             |                   |                 |                |
| 108419-35-8 | Oxo-Tridecyl Acetate.   | NAv           | NAv           |                                   | NAv                 | NAv               |                | 2                                 |                |              | 1                 |                   |                 |                |
| 14808-60-7  | Quartz  | 0.05          | 0.1           | mg/m3 as<br>Resp. Dust            | NAv                 | NAv               |                |                                   |                |              |                   | 11                | 0.1             | 0.1            |
| 112926-00-8 | Amorphous Precipitated Silica                                 | 10            | 6             | mg/m3 as Dust                     | NAv                 | NAv               |                |                                   |                |              |                   |                   |                 | 1              |
| 14464-46-1  | Cristobalite  | 0.05          | 0.05          | mg/m3 as<br>Resp. Dust            | NAv                 | NAv               |                | 0.1                               | 0.1            | 0.2          | 0.2               |                   |                 |                |
| 1332-58-7   | Kaolin  | 2             | 5             | mg/m3 as<br>Resp. Dust            | NAv                 | NAv               |                | < 2 % may be added due to tinting |                |              |                   |                   |                 |                |
| 14807-96-6  | Talc  | 2             | 2             | mg/m3 as<br>Resp. Dust            | NAv                 | NAv               |                | < 2 % may be added due to tinting |                |              |                   |                   | 10              |                |
| 12001-26-2  | Mica  | 3             | 3             | mg/m3 as<br>Resp. Dust            | NAv                 | NAv               |                |                                   |                |              |                   | 4                 |                 |                |
| 471-34-1    | Calcium Carbonate.  | 10            | 15[5]         | mg/m3 as Dust<br>[Resp. Fraction] | NAv                 | NAv               |                |                                   |                |              |                   | 11                | 26              |                |
| 13463-67-7  | Titanium Dioxide.   | 10            | 10[5]         | mg/m3 as Dust<br>[Resp. Fraction] | NAv                 | NAv               |                | 23                                | 16             | 6            | 0 - 5             | 9                 | 9               |                |
| 1314-13-2   | Zinc Oxide  | 10            | 10[5]         | mg/m3 as Dust<br>[Resp. Fraction] | NAv                 | NAv               |                |                                   |                |              |                   | 1                 |                 |                |
| 1333-86-4   | Carbon Black.   | 3.5           | 3.5           | mg/m3                             | NAv                 | NAv               |                | 0 - 2                             | 0 - 2          | 0 - 2        | 0 - 2             |                   |                 |                |
|             | § Zinc Compound. [% Zinc]                                     |               |               |                                   |                     |                   |                |                                   |                |              |                   | 2 [1.4]           |                 | 4 [2.4]        |
|             | § Barium Compound. [% Barium]                                 |               |               |                                   |                     |                   |                |                                   |                |              |                   |                   | 5 [2.6]         |                |
|             | Weight per Gallon (lbs.)                                      |               |               |                                   |                     |                   |                | 10.67                             | 10.03          | 9.28         | 8.80              | 11.19             | 11.46           | 9.43           |
|             | Solids by Weight (%)  |               |               |                                   |                     |                   |                | 52.7                              | 48.3           | 42.0         | 38.3              | 57.7              | 61.2            | 31.7           |
|             | Solids by Volume (%)  |               |               |                                   |                     |                   |                | 39.3                              | 37.6           | 35.3         | 34.5              | 43.0              | 46.2            | 21.9           |
|             | Percent Water   |               |               |                                   |                     |                   |                | 39.0                              | 44.8           | 49.7         | 53.3              | 40.7              | 33.4            | 65.2           |
|             | VOC (Volatile Organic Compounds) Emitted - lbs./gal.          |               |               |                                   |                     |                   |                | 0.86                              | 0.66           | 0.74         | 0.71              | 0.16              | 0.60            | 0.28           |
|             | VOC Less Water & Federally Exempt Solvents - lbs./gal.        |               |               |                                   |                     |                   |                | 1.72                              | 1.44           | 1.67         | 1.63              | 0.35              | 1.12            | 1.10           |
|             | Flash Point (°F)  |               |               |                                   |                     |                   |                | None                              | None           | None         | None              | None              | None            | None           |
|             | HMIS (NFPA) Rating (health - flammability - reactivity)       |               |               |                                   |                     |                   |                | 2* - 0 - 0                        | 2* - 0 - 0     | 2* - 0 - 0   | 2* - 0 - 0        | 1* - 0 - 0        | 2* - 0 - 0      | 2* - 0 - 0     |

P  
E  
R  
C  
E  
N  
T  
  
B  
Y  
  
W  
E  
I  
G  
H  
T

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

**Section 3 — Hazards Identification**

**ROUTES OF EXPOSURE** - Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

**EFFECTS OF OVEREXPOSURE** - Irritation of eyes, skin and upper respiratory system. In a confined area vapors in high concentration may cause headache, nausea or dizziness.

**SIGNS AND SYMPTOMS OF OVEREXPOSURE** - Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE** - None generally recognized.

**CANCER INFORMATION** - For complete discussion of toxicology data refer to Section 11.

**Section 4 — First Aid Measures**

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Do not induce vomiting. Get medical attention immediately.

**Section 5 — Fire Fighting Measures**

|                    |            |            |
|--------------------|------------|------------|
| <b>FLASH POINT</b> | <i>LEL</i> | <i>UEL</i> |
| See TABLE          | N.A.       | N.A.       |

**FLAMMABILITY CLASSIFICATION** - Not Applicable

**EXTINGUISHING MEDIA** - Carbon Dioxide, Dry Chemical, Alcohol Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS** - Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES** - Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**Section 6 — Accidental Release Measures**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED** - Remove all sources of ignition.

Ventilate the area. Remove with inert absorbent.

**Section 7 — Handling and Storage**

**STORAGE CATEGORY** - Not Applicable

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING** - Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

**Section 8 — Exposure Controls/Personal Protection**

**PRECAUTIONS TO BE TAKEN IN USE** - Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), 3 mg./m3 (respirable fraction), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).

**VENTILATION** - Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION** - If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES** - Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

**EYE PROTECTION** - Wear safety spectacles with unperforated sideshields.

**Section 9 — Physical and Chemical Properties**

|                                 |              |                            |                   |
|---------------------------------|--------------|----------------------------|-------------------|
| <b>PRODUCT WEIGHT</b>           | See TABLE    | <b>EVAPORATION RATE</b>    | Slower than ether |
| <b>SPECIFIC GRAVITY</b>         | 1.03 - 1.38  | <b>VAPOR DENSITY</b>       | Heavier than air  |
| <b>BOILING POINT</b>            | 212 - 545 °F | <b>MELTING POINT</b>       | Not Available     |
| <b>VOLATILE VOLUME</b>          | 53 - 78 %    | <b>SOLUBILITY IN WATER</b> | Not Available     |
| <b>PHOTOCHEMICALLY REACTIVE</b> | No           | <b>pH</b>                  | 8.5 - 9.5         |

**Section 10 — Stability and Reactivity**

**STABILITY** - Stable

**CONDITIONS TO AVOID** - None known.

**INCOMPATIBILITY** - None known.

**HAZARDOUS DECOMPOSITION PRODUCTS** - By fire: Carbon Dioxide, Carbon Monoxide, Oxides of Metals in Section 2

**HAZARDOUS POLYMERIZATION** - Will not occur

**Section 11 — Toxicological Information**

**CHRONIC Health Hazards** - Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in the following products may cause adverse effects to the following organ systems:

- *B66W100, B66T204, B66W200* liver, urinary
- *B71Y1* liver, urinary, blood forming

Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.

**Section 12 — Ecological Information** - No data available.**Section 13 — Disposal Considerations**

**WASTE DISPOSAL METHOD** - Waste from B66W1 Primer may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for extractability to determine the applicable EPA hazardous waste numbers.

Waste from the other products listed on this sheet is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate all products in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**Section 14 — Transport Information** - No data available.**Section 15 — Regulatory Information**

**CALIFORNIA PROPOSITION 65** - WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION** - All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

**Section 16 — Other Information**

These products have been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.