



Material Safety Data Sheet

Document Code: SuperPaint-Int
Version: 03

Date of Preparation
December 30, 2003

Section 1 - Product and Company Identification

PRODUCT NAME & NUMBERS

SUPERPAINT® Interior Latex Flat
 Luminous White A86W17 A86W217
 Extra White A86W51 A86W251
 Deep Base A86W53 A86W253
 Pure White (A86W14)
 Midtone Base (A86W15)
 Deeptone Base (A86W16)

HMIS CODES

Health 2*
 Flammability 0
 Reactivity 0

SUPERPAINT® Interior Latex Satin

Luminous White A87W40 A87W240
 Extra White A87W51 A87W251
 Deep Base A87W53 A87W253
 Pure White (A87W41)
 Midtone Base (A87W42)
 Deeptone Base (A87W43)

SUPERPAINT® Interior Latex Semi-Gloss

Luminous White A88W17 A88W217
 Extra White A88W51 A88W251
 Deep Base A88W53 A88W253
 Pure White (A88W14)
 Midtone Base (A88W15)
 Deeptone Base (A88W16)

MANUFACTURER'S NAME
 THE SHERWIN-WILLIAMS COMPANY
 101 Prospect Avenue N.W.
 Cleveland, OH 44115

EMERGENCY TELEPHONE NO.
 (216) 566-2917
 INFORMATION TELEPHONE NO.
 (216) 566-2902

Section 2 - Composition/Information on Ingredients

% WT.	CAS No.	Ingredient Name	Vapor Pressure
0-3	112-34-5	2- (2-Butoxyethoxy) -ethanol ACGIH TLV Not Established OSHA PEL Not Established	0.1 mm
1-6	107-21-1	Ethylene Glycol. ACGIH TLV 50 ppm CEILING OSHA PEL 50 ppm CEILING	0.1 mm
0-0.1 (in Flat only)	14808-60-7	Quartz ACGIH TLV 0.05 mg/m3 as Respirable Dust OSHA PEL 0.1 mg/m3 as Respirable Dust	
0-2	14464-46-1	Cristobalite ACGIH TLV 0.05 mg/m3 as Respirable Dust OSHA PEL 0.05 mg/m3 as Respirable Dust	

Section 2 – Composition/Information on Ingredients (continued)

% WT.	CAS No.	Ingredient Name	Vapor Pressure
0-3	12001-26-2	Mica	
	(in Flat only)	ACGIH TLV 3	mg/m3 as Respirable Dust
		OSHA PEL 3	mg/m3 as Respirable Dust
1-22	471-34-1	Calcium Carbonate.	
		ACGIH TLV 10	mg/m3 as Dust
		OSHA PEL 15	mg/m3 Total Dust
		OSHA PEL 5	mg/m3 Respirable Fraction
4-25	13463-67-7	Titanium Dioxide.	
		ACGIH TLV 10	mg/m3 as Dust
		OSHA PEL 10	mg/m3 Total Dust
		OSHA PEL 5	mg/m3 Respirable Fraction
<3% due to tinting	14807-96-6	Talc	
		ACGIH TLV 2	mg/m3 as Respirable Dust
		OSHA PEL 2	mg/m3 as Respirable Dust
<1% due to tinting	1333-86-4	Carbon Black.	
		ACGIH TLV 3.5	mg/m3
		OSHA PEL 3.5	mg/m3

Section 3 – Hazards Identification

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

In a confined area vapors in high concentration may cause headache, nausea or dizziness.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE - None generally recognized.

CANCER INFORMATION-For Complete Discussion of Toxicology Data Refer to Section 11.

Section 4 – First Aid Measures

EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.
Keep warm and quiet.

INGESTION: Do not induce vomiting.
Get medical attention immediately.

Section 5 – Fire Fighting Measures

FLASH POINT LEL UEL
None N.Ap. N.Ap.

FLAMMABILITY CLASSIFICATION
Not Applicable

EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 - Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate and remove with inert absorbent.

Section 7 - Handling and Storage

DOL STORAGE CATEGORY - Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 8 - Exposure Controls/Personal Protection

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

These coatings may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m³ (total dust), 3 mg./m³ (respirable fraction), OSHA PEL 15 mg./m³ (total dust), 5 mg./m³ (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION - Wear safety spectacles with unperforated sideshields.

Section 9 – Physical and Chemical Properties

PRODUCT WEIGHT	10-12 lb/gal	EVAPORATION RATE	Slower than Ether
SPECIFIC GRAVITY	1.16-1.47	VAPOR DENSITY	Heavier than Air
BOILING POINT	212-500 °F	MELTING POINT	N.A.
VOLATILE VOLUME	56-69 %	SOLUBILITY IN WATER	N.A.
pH	9.2-9.5		
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)			
0.6-1.5 lb/gal	Less Federally Exempt Solvents		
0.3-0.7 lb/gal	Emitted VOC		

Section 10 – Stability and Reactivity

STABILITY - Stable

CONDITIONS TO AVOID - None known.

INCOMPATIBILITY - None known.

HAZARDOUS DECOMPOSITION PRODUCTS - By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION - Will not occur

Section 11 – Toxicological Information

CHRONIC HEALTH HAZARDS

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data, however, there is insufficient evidence in humans for its carcinogenicity.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

Ethylene Glycol is considered an animal teratogen. It has been shown to cause birth defects in rats and mice at high doses when given in drinking water or by gavage. There is no evidence to indicate it causes birth defects in humans.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Rats exposed to titanium dioxide dust at 250 mg./m³ developed lung cancer, however, such exposure levels are not attainable in the workplace.

TOXICOLOGY DATA

CAS No.	Ingredient Name			
112-34-5	2- (2-Butoxyethoxy) -ethanol			
	LC50	RAT	4HR	Not Established
	LD50	RAT		5660 mg/kg
107-21-1	Ethylene Glycol.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		4700 mg/kg
14808-60-7	Quartz			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
14464-46-1	Cristobalite			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
12001-26-2	Mica			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
471-34-1	Calcium Carbonate.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established

13463-67-7	Titanium Dioxide.			
	LC50	RAT	4HR	Not Established
14807-96-6	LD50	RAT		>7500 mg/kg
	Talc			
1333-86-4	LC50	RAT	4HR	Not Established
	LD50	RAT		Not Established
1333-86-4	Carbon Black.			
	LC50	RAT	4HR	Not Established
	LD50	RAT		>15400 mg/kg

Section 12 – Ecological Information

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 – Disposal Considerations

WASTE DISPOSAL METHOD

Waste from these products is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 – Transport Information

No data available.

Section 15 – Regulatory Information

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
107-21-1	Ethylene Glycol.	max 6	
	Glycol Ethers	max 3	

CALIFORNIA PROPOSITION 65

WARNING: These products contain chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in these products are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 – Other Information

CANADIAN DISTRIBUTOR: *Sherwin-Williams Canada
180 Brunel Rd.
Mississauga, ON L4Z 1T5*

NOTE: These products have been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to these products as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to these products may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.