

# ChemCAS

## Search

serco stainless steel maintainer msds



MSDS 250,000+

MSDS : SERCO WATER BASED STAINLESS STEEL MAINTAINER, 27885  
CAS : 75-28-5  
8012-95-1  
NAME : propane, 2-methyl-; (isobutane)  
mineral oil

Catalog of Chemical Suppliers, Buyers, Custom Synthesis Companies And Equipment Manufacturers  
[ SERCO WATER BASED STAINLESS STEEL MAINTAINER, 27885 75-28-5 8012-95-1 ]

Suppliers:

Not Available

Buyers:

Not Available

### ==== Product Identification =====

MSDS NAME:SERCO WATER BASED STAINLESS STEEL MAINTAINER, 27885

NIIN:00N058734

MSDS Number: BXPFC

=== Responsible Party ===

Company:S. E. RYKOFF & CO

Address:761 TERMINAL ST

City:LOS ANGELES

State:CA

ZIP:90021

Country:US

Info Phone Num:213-622-4131

Emergency Phone Num:213-622-4131

CAGE:3E121

==== Contractor Identification ===

Company:S. E. RYKOFF & CO

Address:761 TERMINAL STREET

Box:City:LOS ANGELES

State:CA

ZIP:90021

Country:US

Phone:213-622-4131 EXT 2643

CAGE:3E121

=====  
Composition/Information on Ingredients  
=====

Name:PROPANE, 2-METHYL-; (ISOBUTANE)  
CAS:75-28-5  
RTECS #:TZ4300000  
Fraction by Wt: 11%  
OSHA PEL:1000 PPM (MFR)  
ACGIH TLV:1000 PPM (MFR)

Name:MINERAL OIL  
CAS:8012-95-1  
RTECS #:PY8030000  
Fraction by Wt: 26%  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3 (MIST)

=====  
Hazards Identification  
=====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:INHALATION:EXCESSIVE INHALATION  
OF VAPORS CAN BE HARMFUL AND MAY CAUSE HEADACHE, DIZZINESS,  
ASPHYXIA, ANESTHETIC EFFECTS AND POSSIBLE UNCONSCIOUSNESS. EYE:MILD  
IRRITATION. SKIN:MAY AGGRAVATE EXISTING SKIN CONDITIONS.  
INGESTION:POSSIBLE CHEMICAL PNEUMONITIS IF ASPIRATED INTO LUNGS,  
NAUSEA. (EFFECTS OF OVEREXPOSURE)  
Explanation of Carcinogenicity:NOT RELEVANT  
Effects of Overexposure:HEALTH HAZARDS:CHRONIC:(EFFECTS DUE TO EXCESSIVE  
EXPOSURE TO THE RAW MATERIALS OF THIS MIXTURE) MAY CAUSE HEADACHES,  
DIZZINESS AND NAUSEA.  
Medical Conditions Aggravated by Exposure:MAY AGGRAVATE EXISTING SKIN  
CONDITIONS.

=====  
First Aid Measures  
=====

Eyes:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATED,  
SEE PHYSICIAN. SKIN:WASH WITH SOAP AND WATER. IF IRRITATED, SEE  
PHYSICIAN. INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF  
NECESSARY. GET MEDICAL AID. INGESTION:INDUCE VOMITING. CALL  
PHYSICIAN IMMEDIATELY.

=====  
Fire Fighting Measures  
=====

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE, WATER. PRODUCT  
IS NON-FLAMMABLE.  
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL  
PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:DO NOT EXPOSE AEROSOLS TO TEMPERATURES  
ABOVE 120F OR THE CONTAINER MAY RUPTURE.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ABSORB WITH SUITABLE MEDIUM.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT PUNCTURE OR INCINERATE  
CONTAINERS. DO NOT STORE AT TEMPERATURES ABOVE 120F.  
Other Precautions:AVOID FOOD CONTAMINATION. KEEP OUT OF REACH OF  
CHILDREN. AVOID BREATHING VAPORS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF VAPOR CONCENTRATION EXCEEDS TLV, USE  
RESPIRATOR APPROVED BY NIOSH/MSHA IN POSITIVE PRESSURE MODE.  
Ventilation:LOCAL EXHAUST:ADEQUATE VENTILATION TO KEEP VAPOR  
CONCENTRATION BELOW TLV.  
Protective Gloves:LATEX, IF SKIN IS EASILY IRRITATED.  
Eye Protection:ANSI APPROVED SAFETY GLASSES .  
Other Protective Equipment:NO SPECIAL CLOTHING REQUIRED.  
Work Hygienic Practices:WASH WITH SOAP AND WATER BEFORE HANDLING FOOD.  
REMOVE CONTAMINATED CLOTHING.

Supplemental Safety and Health  
 SPEC GRAV:CONCENTRATE ONLY=0.960 (H\*20=1). VP:PSIG @ 70F (AEROSOL) MAX  
 60.

===== Physical/Chemical Properties =====

Vapor Pres:SUPP DATA  
 Spec Gravity:SUPP DATA  
 Solubility in Water:SOLUBLE  
 Appearance and Odor:WHITE FOAM WITH LIGHT LEMON FRAGRANCE.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
 STRONG OXIDANTS.  
 Stability Condition to Avoid:OPEN FLAME, WELDING ARCS, HEAT.  
 Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL ACCORDING TO LOCAL, STATE  
 OR FEDERAL REGULATIONS. DO NOT FLUSH TO SEWER. AEROSOL CANS, WITH  
 VENTED ATMOSPHERIC PRESSURE THROUGH NORMAL USE, POSE NO DISPOSAL  
 HAZARD.

Disclaimer (provided with this information by the compiling agencies):  
 This information is formulated for use by elements of the Department  
 of Defense. The United States of America in no manner whatsoever,  
 expressly or implied, warrants this information to be accurate and  
 disclaims all liability for its use. Any person utilizing this  
 document should seek competent professional advice to verify and  
 assume responsibility for the suitability of this information to their  
 particular situation.

\*\*\* END OF RECORD \*\*\*

**Search More** serco stainless steel maintainer msds



**ALL PAGES On Chemical Property IN THIS GROUP**

NAME	CAS
<u>RAPID SEAL 365 (ALL COLORS)</u>	1330-20-7 68515-49-1 1317-65-3 13463-67-7
<u>SLO-ZAP</u>	7085-85-0 9011-14-7
<u>ZAP-A-GAP</u>	7085-85-0 9011-14-7
<u>ZAP LOCK MEDIUM</u>	7085-85-0 9011-14-7
<u>FLEX-ZAP</u>	7085-85-0 9011-14-7
<u>TRAPPER INSECT MONITOR</u>	
<u>TRAPPER LTD</u>	
<u>TRAPPER GLUE</u>	
<u>TRAPPER MOUSE PRO</u>	
<u>MHB-BK, 87368 CLEAR</u>	4253-34-3
<u>MHB-BK, 87370 BLACK</u>	4253-34-3
<u>MHB-BK, 87369 WHITE</u>	4253-34-3
<u>PLASTIC KOTE ACRYLIC VELVET FINISH PAINT, 21-006</u>	25265-77-4 1317-65-3 107-21-1 68476-25-5 1332-58-7

<u>PLASTIC KOTE ACRYLIC VELVET FINISH PAINT, 21-007</u>	13463-67-7 25265-77-4 1317-65-3 107-21-1 68476-25-5 1332-58-7 13463-67-7
<u>PLASTIC KOTE ACRYLIC VELVET FINISH PAINT, 21-012</u>	25265-77-4 1317-65-3 107-21-1 68476-25-5 13463-67-7
<u>PLASTIC KOTE ACRYLIC VELVET FINISH PAINT, 21-014</u>	25265-77-4 1317-65-3 107-21-1 68476-25-5 1332-58-7 13463-67-7
<u>LUBRIPLATE SUPER GPO 30</u>	
<u>LUBRIPLATE SUPER GPO 15W-40</u>	
<u>LUBRIPLATE SUPER GPO 10W-30</u>	
<u>WINDSHIELD WASHER SOLVENT, M5-49</u>	67-63-0 111-76-2
<u>WINDSHIELD WASHER SOLVENT, M5-40</u>	67-63-0 111-76-2
<u>WINDSHIELD WASHER SOLVENT, M5-06</u>	67-63-0 111-76-2
<u>AMMONIA</u>	7732-18-5 1336-21-6
<u>1432, TRI AQUA M &amp; E YELLOW ENAMEL WATER (SUPDAT)</u>	78-92-2 111-76-2 7664-41-7
<u>PASTE WOOD FILLER</u>	64742-88-7 61789-51-3
<u>PAINT ETCH</u>	75-09-2 67-56-1 67-63-0
<u>TACK CLOTH</u>	
<u>CAREFREE</u>	
<u>UNICOAT</u>	107-21-1
<u>SPRINT PEN 720-BLACK, 7209-H7</u>	
<u>SPRINT PEN 720-BLUE, 7203-H7</u>	
<u>SPRINT PEN 720-RED, 7202-H7</u>	
<u>SPRINT PEN 720-GREEN, 7205-H7</u>	
<u>AMERI-BRASS WIRE</u>	7440-50-8 7440-66-6 7439-92-1
<u>NO 7 CHROME POLISH &amp; CLEANER 1012N</u>	112945-52-5 1113-38-8 64742-88-7
<u>SEALING CEMENT - 33S</u>	14808-60-7 1344-09-8 16893-85-9
<u>ECOLINK 2005 CFC-FREE CONTACT CLEANER</u>	1717-00-6
<u>DIETHYLENE GLYCOL 99%</u>	111-46-6
<u>SERCO WATER BASED STAINLESS STEEL MAINTAINER, 27885</u>	75-28-5 8012-95-1
<u>SERCO LIQUID BLEACH; 26921</u>	7681-52-9
<u>SURE COAT, WHITE OR GRAY</u>	65997-15-1 1592-23-0 1305-62-0 112945-52-5 7647-14-5

EMB-4011-R, MATTE-BACK POLYESTER FILM FOR (SUP DAT)

FALT-FIL, 4023

NU-CONCEPT, 0122

HYSPIN R & O OIL 10, AMFLO 1220

HAZE GRAY RUSTLESS ENAMEL, 2419

CALCO CHINOLINE YELLOW SDS

SPIRIT DUPLICATING FLUID

ALUMINUM OXIDE

METHACRYLIC ACID

13463-67-7  
9004-58-4  
25213-24-5  
14808-60-7  
25038-59-9  
112945-52-5  
13463-67-7  
64742-15-0  
1317-65-3  
9002-93-1  
64742-46-7  
64742-58-1  
64642-88-7  
64742-95-6  
64742-89-8  
67-56-1  
78-83-1

67-56-1  
1344-28-1  
13463-67-7  
112945-52-5  
79-41-4

Free MSDS Search ( Providing 250, 000+ Material Properties )  
Chemcas Copyright Reserved  
Last modified: 06/15/2012 15:25:47