



Spartan Chemical Company, Inc.

Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

LUBE-ALL (AEROSOL)

Product Number: 6730

Spartan Chemical Company, Inc.

1110 Spartan Drive

Maumee, OH 43537

Product Division:

Janitorial

Product/Technical
Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill
Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description:		ORM-D, Consumer commodity, cleaning compounds, aerosol, n.o.s.	
NFPA Ratings:		HMIS Ratings:	
Health:	1- Slight	Health:	*1 - Slight; Chronic Hazard
Fire:	3 - Serious	Fire:	3 - Serious
Reactivity:	1- Slight	Reactivity:	1- Slight
		Pers. Prot. Equip.:	See Section VIII

▼ SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

Chemical Name(s)	% W	CAS Registry No.	Table Z- 1 - A			NTP, IARC or OSHA Carcinogen
			TWA mg/m ³	STEL mg/m ³	CEILING mg/m ³	
Petroleum distillate	20-30	64741-89-5	5 (oil mist)	Not Established	Not Established	No
Petroleum distillate	20-30	64741-88-4	5 (oil mist)	Not Established	Not Established	No
Petroleum distillate	10-15	64742-47-8	Not Established	Not Established	Not Established	No
Petroleum distillate	10-15	64742-52-5	5 (oil mist)	Not Established	Not Established	No
Propane	10-15	74-98-6	1800	Not Established	Not Established	No
Isobutane	10-15	75-28-5	1800 (ACGIH)	Not Established	Not Established	No
Petroleum distillate	1-5	64742-65-0	5 (oil mist)	Not Established	Not Established	No
Polytetrafluorethylene	< 1.0	9002-84-0	5 (respirable dust - Dupont)	Not Established	Not Established	No

▼ SECTION III: PHYSICAL DATA

Boiling Point:	> 200 °F	Vapor Pressure:	Unknown
Vapor Density (AIR = 1):	Unknown	Solubility in Water:	Negligible
pH:	NA	Specific Gravity (H ₂ O=1):	NA
Evaporation Rate (but.ace.=1):	<1	Percent Solid by Weight:	1-5
Physical State:	Aerosol can (pressurized liquid)		
Appearance & Odor:	Oily liquid, negligible fragrance		

▼ SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point:	Propellant: < 0 °F	Method Used:	Estimate
Flammable Limits:	Not established Lower Explosive Limit: 0.6 % Upper Explosive Limit: 9.5%	Flame Extension:	> 28 Inches NFPA 30B Level 3 Aerosol
Extinguishing Media:	Carbon dioxide, Dry chemical,		
Special Fire Fighting Procedures:	Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat. Wear a full face positive pressure self contained breathing apparatus when fighting fires.		
Unusual Fire & Explosive Hazards:	Material is highly volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors, static discharge or other ignition sources at locations distant from material handling point.		

▼ SECTION V: HEALTH HAZARD DATA

Threshold Limit Value:	Not Established	Primary Routes of Entry:	Inhalation, Skin Contact, Eyes & Oral
Effects of Overexposure-Conditions to Avoid:	<p>Harmful or Fatal if Swallowed. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.</p> <p>Harmful if Inhaled. Inhalation of vapors may cause central nervous system effects including dizziness, weakness, fatigue, nausea & headache. Prolonged exposure to propellant vapors above the OSHA permissible exposure limits may result in kidney and liver damage. The intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.</p> <p>Causes Eye & Skin Irritation. Symptoms include pain, redness, swelling of the conjunctiva and tearing. Avoid breathing product vapors or mists. Avoid contact with eyes and skin. Do not swallow. Wash thoroughly after handling.</p>		
Conditions Aggravated by Use:	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis.		

Emergency & First Aid Procedures:

Eyes:	Flush eyes with water for at least 15 minutes. Remove contact lenses. Get medical attention.
Skin:	Wash thoroughly with soap and water. Get medical attention if irritation persists.
Ingestion:	Do not induce vomiting. Call a physician immediately.
Inhalation:	Move person to fresh air. Get medical attention if irritation persists.

▼ SECTION VI: REACTIVITY DATA

Stability:	Stable	Incompatible Materials:	Avoid contact with strong oxidizing agents; strong alkalis and strong mineral acids.
Hazardous Decomposition Products:	Burning can produce carbon monoxide, carbon dioxide and phosgene gas	Hazardous Polymerization:	Will Not Occur

▼ SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:	Ventilate area. Remove all sources of ignition. Clean up with inert materials and dispose of in accordance with all local, state and federal regulations.
Waste Disposal Method:	Do not puncture or incinerate aerosol containers. Empty containers may be disposed of through normal channels. Full or partially filled containers are considered hazardous waste.

▼ SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Not normally required when good general ventilation is provided. However, if exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered.
Ventilation:	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.
Protective Gloves(Specify Type):	Wear impervious gloves for prolonged or repeated contact.
Eye Protection(Specify Type):	Splash goggles are recommended to prevent eye contact.
Other Protective Equipment:	See 29 CFR 1910.132-138 for further reference.

▼ SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing:	Do not puncture or incinerate container. Do not use or store product near heat, sparks or open flame. Do not store in direct sunlight or above 120 F. High temperatures may cause container to burst. Wash thoroughly after handling.
Other Precautions:	Keep out of reach of children.

© SCC 11/01/2007
LUBE-ALL (AEROSOL)

Name: Ronald T. Cook
Effective 11/01/2007
Date:

Title: Manager, Regulatory Affairs
Supercedes: 01/25/2005

Ref: 29 CFR 1910.1200 (OSHA) Changes: General update

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.