

MATERIAL SAFETY DATA SHEET

01-05-95

HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	

IDENTITY

(As Used on Label and List) **ORR-LAC STANDARD AND FARM IMPLEMENT COLORS, ENGINE PAINTS**

Section I

Silver #998

Manufacturer's Name	SPRAY PRODUCTS CORPORATION	Emergency Telephone Number	(800) 427-656
Address	P.O. BOX 737	CHEMTREC: THIS NUMBER IS ONLY IN THE CASE OF EMERGENCIES INVOLVING A SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT INVOLVING CHEMICAL	
	NORRISTOWN, PA 19404		
	(610) 277-1010		

HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO.	ORM-D, CONSUMER COMMODITY
ADDITIONAL HAZARD CLASSES	NOT APPLICABLE
CHEMICAL FAMILY	NOT APPLICABLE
FORMULA	NOT APPLICABLE

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity/Common Name(s) - CAS #	ACGIH TLV	Other Limits Recommended	%
* ACETONE 67-64-1	750		40.0
* TOLUENE 108-88-3	100		12.0
* METHYL ISOBUTYL KETONE 108-10-1	50		10.0
PROPYLENE GLYCOL MONO METHYL (cont.) ETHER ACETATE 108-65-6	NOT ESTAB		7.0
ISOBUTYL ALCOHOL 78-83-1	50		2.0
PROPANE 74-98-6	1000		15.0
RESIN AND PIGMENTS UNKNOWN	UNKNOWN		14.0

WARNING: Under Proposition 65, this product contains a chemical known to the State of California to cause birth defects or other reproductive harm

* SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III AND 40CFR PART 372

Section III - Physical/Chemical Characteristics

Boiling Point	PROPANE -43.7 F	Specific Gravity (water = 1)	SOLVENT MIX 0.819
Vapor Pressure (mm Hg.)	SOLVENT MIX 149.8	Melting Point	SOLVENT MIX -119 F
Vapor Density (AIR = 1)	SOLVENT MIX 2.16	Evaporation Rate (Butyl Acetate = 1)	SOLVENT MIX 4.65
Solubility in Water	SOLVENT MIX - APPRECIABLE		
Appearance and Odor	COLOR OF PAINT / KETONE ODOR		

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	PROPANE -156F TCC	Flammable Limits	PROPANE LEL 2.2 UEL 8.9
Extinguishing Media	FOAM, CO2, DRY CHEMICALS		
Special Fire Fighting Procedures	HANDLE AS EXTREMELY FLAMMABLE LIQUID. COOL CONTAINERS EXPOSED TO HEAT WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS.		
Unusual Fire and Explosion Hazards	CONTENTS UNDER PRESSURE.		

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid KEEP AWAY FROM HEAT, SPARKS OR OPEN FLAME. DO NOT STORE ABOVE 120 F.
	Stable	X	
Incompatibility (Materials to Avoid)			
Hazardous Decomposition or Byproducts CO, CO2 MAY BE FORMED DURING COMBUSTION.			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will not Occur	X	

Section VI - Health Hazard Data

Routes of Entry:	Inhalation? YES	Skin? YES	Ingestion? UNUSUAL
Health Hazards (Acute and Chronic) REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.			
Carcinogenicity:	NIP? NO	IARC Monograph? NO	OSHA Regulated? NO
Signs and Symptoms of Exposure HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF CONCIIOUSNESS.			
Medical Conditions Generally Aggravated by Exposure MAY CAUSE DEFATTING AND DRYING OF SKIN. MAY IRRITATE MUCOUS MEMBRANES OF RESPIRATORY TRACT. OVEREXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION.			

Emergency and First Aid Procedures
 INHALATION: REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. SKIN CONTACT: WASH WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CALL PHYSICIAN. INGESTION: DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled ELIMINATE SOURCES OF HEAT OR IGNITION - VENTILATE AREA. APPLY ABSORBENT MATERIAL TO SPILL AREA.	
Waste Disposal Method ABSORBING MATERIAL OR DEFECTIVE CONTAINERS SHOULD BE DISPOSED AT RCRA APPROVED TS & D FACILITY AND ACCORDING TO FEDERAL, STATE, AND LOCAL LAWS.	
Precautions to Be Taken in Handling and Storing EXTREMELY FLAMMABLE. STORE AND USE AWAY FROM ALL HEAT AND IGNITION SOURCES. USE ADEQUATE VENTILATION. HAZARDOUS WASTE NUMBER: F003, D001.	
Other Precautions CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 F. DO NOT PUNCTURE OR INCINERATE.	

Section VIII - Control Measures

Respiratory Protection (Specify Type) /USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR IF VENTILATION IS INADEQUATE.		
Ventilation	Local Exhaust YES	Special NONE
	Mechanical (General) IF REQUIRED	Other NONE
Protective Gloves NEOPRENE, IF SUBJECTED TO EXPOSURE.	Eye Protection CHEMICAL GOGGLES OR SAFETY GLASSES.	
Other Protective Clothing or Equipment NONE		
Work/Hygiene/Maintenance Practices AVOID BREATHING VAPOR. AVOID EYE AND SKIN EXPOSURE. KEEP OUT OF REACH OF CHILDREN.		