

MATERIAL SAFETY DATA SHEET

956

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME SPRAY PRODUCTS CORPORATION		EMERGENCY TELEPHONE NO. 215/277-1010
ADDRESS (Number, Street, City, State, and ZIP Code) P.O. BOX 737, NORRISTOWN, PA 19404		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS CLEAR #470, #370, #970
CHEMICAL FAMILY	FORMULA	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE ACRYLOID (ROHM-HAAS)	10		METALLIC COATINGS		
SOLVENTS	75	::	FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES			OTHERS		
OTHERS PROPANE	15				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE				4	100
MIBK				8	100
ACETONE				34	1000
METH. CHLORIDE				16	500
TOLUENE				13	100
					75 1800

SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	-43.7	SPECIFIC GRAVITY (H ₂ O=1)	.801
VAPOR PRESSURE (mm Hg.)	70	PERCENT. VOLATILE BY VOLUME (%)	85
VAPOR DENSITY (AIR=1)	1.28	EVAPORATION RATE (_____ =1)	8.6
SOLUBILITY IN WATER	MODERATE		
APPEARANCE AND ODOR			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	T.C.C. -138°F.	FLAMMABLE LIMITS	2.2 ^{Lel}	8.9 ^{Uel}
EXTINGUISHING MEDIA	FOAM; CO ₂ , DRY CHEMICALS			
SPECIAL FIRE FIGHTING PROCEDURES	HANDLE AS EXTREMELY FLAMMABLE LIQUID.			
UNUSUAL FIRE AND EXPLOSION HAZARDS				
CONTENTS UNDER PRESSURE				
DO NOT STORE ABOVE 120°F.				

SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	700 P.P.M.
EFFECTS OF OVEREXPOSURE	ANESTHESIA, HEADACHE, NAUSEA, DIZZINESS, "HANGOVER", AND RECOVER.
EMERGENCY AND FIRST AID PROCEDURES	REMOVE VICTIM TO FRESH AIR. IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION.

SECTION VI - REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	SPARKS, OPEN FLAME
INCOMPATIBILITY (Materials to avoid)			
HAZARDOUS DECOMPOSITION PRODUCTS			
STRONG OXIDIZING AGENTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	
AVOID OPEN FLAMES OR SPARK SOURCE / PROVIDE ADEQUATE VENTILATION	
WASTE DISPOSAL METHOD	
EVAPORATE OR FLUSH WITH WATER REMOVE TO CONTAINER.	

SECTION VIII - SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type)			
NORMALLY NOT REQUIRED			
VENTILATION	LOCAL EXHAUST	DESIRABLE	SPECIAL
	MECHANICAL (General)	AS REQUIRED	OTHER
PROTECTIVE GLOVES		EYE PROTECTION	
NORMALLY NOT REQUIRED		NORMALLY NOT REQUIRED	
OTHER PROTECTIVE EQUIPMENT			

SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	
EXTREMELY FLAMMABLE - CONTENTS	
UNDER PRESSURE. DO NOT STORE ABOVE 120 ⁰ F. KEEP FROM OPEN FLAMES OR SPARK.	
OTHER PRECAUTIONS	
DO NOT PUNCTURE OR INCINERATE CAN.	