

# MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION	
<b>NFPA Rating:</b> Health-2; Flammability-2; Reactivity-0; Special-0 <b>Manufactured For:</b> Triple S <b>Address:</b> 2 Executive Park Dr. <b>Address:</b> Billerica, MA 01862 <b>Phone:</b> 978-667-7900	<b>HMSIS Rating:</b> Health-2; Flammability-2; Reactivity-0; Personal Protection-B <b>DOT Hazard Classification:</b> ORM-D <b>Identity</b> (trade name as used on label): <b>SSS Metal Cleaner &amp; Polish</b> <b>MSDS Number:</b> 141 <b>Revision:</b> 12 <b>Date Prepared:</b> 08/28/96 <b>Prepared By:</b> LF <b>Information Calls:</b> 978-667-7900
<b>EMERGENCY RESPONSE NUMBER: 1-800-255-3924</b> <b>NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA</b>	

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
PETROLEUM DISTILLATE	64742-54-7	Yes	5mg/M3	5mg/M3	d
PETROLEUM DISTILLATE	64742-47-8	No	100	100	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
<b>Boiling Point:</b> N/A	<b>Specific Gravity (H2O=1):</b> Concentrate Only = .856
<b>Vapor Pressure:</b> PSIG @ 70°F (Aerosols): Max.60	<b>Vapor Pressure (Non-Aerosols)(mm Hg and Temperature):</b> N/A
<b>Vapor Density (Air = 1):</b> N/E	<b>Evaporation Rate ( = 1):</b> N/E
<b>Solubility in Water:</b> Insoluble	<b>Water Reactive:</b> No
<b>Appearance and Odor:</b> Clear liquid, lemon fragrance.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA			
<b>FLAMMABILITY</b> as per USA FLAME PROJECTION TEST (aerosols) <b>FLAMMABLE</b> >18 Inches	<b>Auto Ignition Temperature</b> N/E	<b>Flammability Limits in Air by % in Volume:</b> % LEL: N/E      % UEL: N/E	
<b>FLASH POINT AND METHOD USED (non-aerosols):</b> N/A		<b>EXTINGUISHER MEDIA:</b> Foam, dry chemical, carbon dioxide.	
<b>SPECIAL FIRE FIGHTING PROCEDURES:</b> Self-contained breathing apparatus.			
<b>Unusual Fire &amp; Explosion Hazards:</b> Do not expose aerosols to temperatures above 130°F or the container may rupture.			

SECTION 4 - REACTIVITY HAZARD DATA	
<b>STABILITY</b> <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE	<b>HAZARDOUS POLYMERIZATION</b> <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR
<b>Incompatibility (Mat. to avoid):</b> Strong oxidizers.	<b>Conditions to Avoid:</b> Open flame, welding arcs, heat, sparks.
<b>Hazardous Decomposition Products:</b> CO, CO2.	

SECTION 5 - HEALTH HAZARD DATA	
<b>PRIMARY ROUTES OF ENTRY:</b> <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS	

<b>ACUTE EFFECTS</b>	
<b>Inhalation:</b> Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.	
<b>Eye Contact:</b> Mild irritation.	<b>Skin Contact:</b> Mild irritation.
<b>Ingestion:</b> Possible chemical pneumonitis if aspirated into lungs. Nausea.	
<b>CHRONIC EFFECTS:</b> (Effects due to excessive exposure to the raw materials of this mixture) May cause cardiac abnormality, liver abnormalities, lung and kidney damage.	
<b>Medical Conditions Generally Aggravated by Exposure:</b> May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES	
<b>Eye Contact:</b> Flush with water for 15 minutes. If irritated, seek medical attention.	
<b>Skin Contact:</b> Wash with soap and water. If irritated, seek medical attention.	
<b>Inhalation:</b> Remove to fresh air. Resuscitate if necessary. Get medical attention.	
<b>Ingestion:</b> <b>DO NOT INDUCE VOMITING.</b> Drink two large glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
<b>Respiratory Protection (specify type):</b> If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.	
<b>Protective Gloves:</b> Polyethylene gloves	<b>Eye Protection:</b> Safety glasses recommended.
<b>Ventilation Requirements:</b> Adequate ventilation to keep vapor concentration below TLV.	
<b>Other Protective Clothing &amp; Equipment:</b> None	
<b>Hygienic Work Practices:</b> Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
<b>Steps To Be Taken If Material Is Spilled Or Released:</b> Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. DO NOT FLUSH TO SEWER.	
<b>Waste Disposal Methods:</b> Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.	
<b>Precautions To Be Taken In Handling &amp; Storage:</b> Do not puncture or incinerate containers. Do not store at temperatures above 130°F.	
<b>Other Precautions &amp;/or Special Hazards:</b> <b>KEEP OUT OF REACH OF CHILDREN.</b> Avoid food contamination. Avoid breathing vapors. Remove ignition sources.	

*We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.*

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

**THIS MSDS IS CURRENT AS OF JANUARY 10, 2000.** The DATE PREPARED section is the original date assembled and remains current until a change is necessary.