

=====  
Safety Information  
=====

MSDS

[TOP](#)

FSC: 8010

MSDS Date: 07/24/1990

MSDS Num: BMLMS

Submitter: F BT

LIIN: 00F021307

Tech Review: 02/06/1992

Status CD: C

Product ID: HPX-7 TRU-TEST SUPREME WEATHERALL FLAT ACRYLIC LATEX PAINT

MFN: 01

Article: N

Kit Part: N

Responsible Party

Cage: TRUTE

Name: TRU-TEST MANUFACTURING CO

Address: 201 JANDUS RD

Box: N/K

City: CARY

State: IL

Zip: 60013

Country: NK

Info Phone Number: (708) 639-5383

Emergency Phone Number: (800) 228-5635

Preparer's Name: N/P

Proprietary Ind: N

Review Ind: Y

Published: Y

Special Project CD: N

=====  
Preparer  
Co. when other than Responsible Party Co.  
=====

Preparer

[TOP](#)

Cage: TRUTE

Assigned Ind: N

Name: TRU-TEST MANUFACTURING CO

Address: 201 JANDUS RD

Box:

City: CARY

State: IL

Zip: 60013

=====  
Contractor  
Summary  
=====

Contractor

[TOP](#)

Cage: TRUTE

Name: TRU-TEST MANUFACTURING CO

Address: 201 JANDUS RD

City: CARY

State: IL

Zip: 60013

Country: US

Phone: 708-639-5383

=====  
Ingredients  
=====

[TOP](#)

Cas: 66402-68-4

Code: M

RTECS #:

Code: X

Name: GROG; CALCIUM-BARIUM PHOSPHOSILICATE \*91-4\*

% Text: 8-13%

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: 15 MG/CUM

Code: M

OSHA  
STEL:

Code:

ACGIH TLV: 20 MG/CUM

Code: M

N/P

Code:

EPA Rpt Qty:

ACGIH  
STEL:  
DOT Rpt  
Qty:

Ozone Depleting Chemical: N

Cas: 107-21-1

Code: M

RTECS #: KW2975000

Code: M

Name: ETHYLENE GLYCOL, GLYCOL

% Text: 1-5%

Environmental Wt:

Other REC Limits: 10 MG/CUM

OSHA PEL: 50 PPM

Code: M

OSHA

Code:

STEL:

ACGIH TLV: C 127 MG/CUM

Code: M

ACGIH N/P

Code:

STEL:

EPA Rpt Qty: 1 LB

DOT Rpt 1 LB

Qty:

Ozone Depleting Chemical: N

Cas: 68855-54-9

Code: M

RTECS #:

Code: X

Name: DIATOMACEOUS EARTH FLUX-CALCINED, NATURAL, SILICA

% Text: 1-5%

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: 80 MG/CUM

Code: M

OSHA

Code:

STEL:

ACGIH TLV: 10 MG/CUM

Code: M

ACGIH N/P

Code:

STEL:

EPA Rpt Qty:

DOT Rpt

Qty:

Ozone Depleting Chemical: N

Cas:

Code: X

RTECS #: 9999999VO

Code: M

Name: VOL ORGANIC CMPD: <200 GM/L

% Text: N/K

Environmental Wt:

Other REC Limits: N/K

OSHA PEL: N/K

Code: M

OSHA

Code:

STEL:

ACGIH TLV: N/K

Code: M

ACGIH N/P

Code:

STEL:

EPA Rpt Qty:

DOT Rpt

Qty:

Ozone Depleting Chemical:

Hazards Data

Health

TOP

LD50 LC50 Mixture N/K

Route Of Entry Inds - Inhalation: YES

Skin: YES

Ingestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO

OSHA: NO

Health Hazards Acute And Chronic

EYES/SKIN: IRRITATION. INHALATION: NOSE, THROAT, MUCOUS MEMBRANE, & RESPIRATORY TRACT IRRITATION.

Explanation Of Carcinogenicity

NONE

Signs And Symptions Of Overexposure

EYES/SKIN: IRRITATION. INHALATION: NOSE, THROAT, MUCOUS MEMBRANE, & RESPIRATORY TRACT IRRITATION.

Medical Cond Aggravated By Exposure

N/K

First Aid

INHALATION: REMOVE TO FRESH AIR. SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER. INGESTION: GIVE 1 OR 2 GLASSES OF WATER TO DILUTE. DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CAS ES.

Spill Release Procedures

DIKE & CONTAIN SPILL W/INERT MATERIAL (SAND, EARTH, ETC.). TRANSFER LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL. KEEP SPILL OUT OF SEWERS & OPEN BODIES OF WATER.

Neutralizing Agent

N/K

Waste Disposal Methods

CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Handling And Storage Precautions

KEEP FROM FREEZING.

Other Precautions

DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN.

Explosion Hazard Information Fire and TOP

Flash Point Method: N/P

Flash Point:

Flash Point Text: N/K

Autoignition Temp:

Autoignition Temp Text: N/A

Lower Limits: N/K

Upper Limits: N/K

Extinguishing Media

FOAM, CO2, DRY CHEMICAL, OR WATER FOG

Fire Fighting Procedures

WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Control Measures TOP

Respiratory Protection

USE MECHANICAL FILTER RESPIRATOR TO REMOVE AIRBORNE PARTICLES OF OVERSPRAY WHEN >TLV.

Ventilation

SUFFICIENT TO KEEP <TLV.

Protective Gloves

AS REQUIRED

Eye Protection

SAFETY GLASSES W/SPLASH GUARDS

Other Protective Equipment

EYEWASH FACILITY, &PROTECTIVE CLOTHING

Work Hygienic Practices

WASH HANDS BEFORE EATING, SMOKING OR USING BATHROOM.

Supplemental Safety and Health

N/K

Physical/Chemical Properties

TOP

HCC:

NRC/State LIC No:

Net Prop WT For Ammo:

Boiling Point:

B.P. Text: 212F

Melt/Freeze Pt:

M.P/F.P Text: N/K

Decomp Temp:

Decomp Text: N/K

Vapor Pres: N/K

Vapor Density: >AIR

Volatile Org Content %:

Spec Gravity: N/K

VOC Pounds/Gallon:

PH: N/K

VOC Grams/Liter:

Viscosity: N/P

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: N/K

Appearance and Odor: VARIES W/COLOR

Percent Volatiles by Volume: N/K

Corrosion Rate: N/K

Reactivity

TOP

Stability Indicator: YES

Stability Condition To Avoid: FREEZING

Materials To Avoid: N/K

Hazardous Decomposition Products: N/K

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization N/K

:

=====  
**Toxicological Information**  
===== TOP

**Toxicological Information:**N/P

=====  
**Ecological Information**  
===== TOP

**Ecological:** N/P

=====  
**Transport Information**  
===== TOP

**Transport Information:**N/P

=====  
**Regulatory Information**  
===== TOP

**Sara Title III Information:** N/P

**Federal Regulatory Information:** N/P

**State Regulatory Information:** N/P

=====  
**Other Information**  
===== TOP

**Other Information:** N/P

=====  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.