
SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION OSHA CLASS II FLASH POINT 105°F LEL 0.9 ()
DOT COMBUSTIBLE LIQUID

EXTINGUISHING MEDIA:

FOAM "ALCOHOL"
FOAM CO2 DRY CHEMICAL WATER FOG OTH

UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers may explode when exposed to extreme heat. Isolate from heat, sparks and open flame.

SPECIAL FIREFIGHTING PROCEDURES Treat as a volatile liquid fire. Water spray may be ineffective. If water is used, fog nozzles are preferable.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE Severe eye irritation, drying of skin. Excessive inhalation causes headache, dizziness and nausea.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None known to Tru-Test Manufacturing Company

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES EYES: Flush with large amounts of water. Seek medical attention.

SKIN: Wash with soap & water.

INHALATION: Remove to fresh air. Use artificial respiration if necessary. Get medical attention.

INGESTION: Do not induce vomiting, keep person warm and quiet. Get medical attention.

SECTION VI - REACTIVITY DATA

STABILITY UNSTABLE STABLE

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS

CONDITIONS TO AVOID Isolate from heat & open flame.

INCOMPATIBILITY (MATERIALS TO AVOID) Avoid contact with strong oxidizing agents.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Contain spill, absorb liquid with clay, sand or floor absorbent. Prevent run-off to sewers, streams or other bodies of water.

WASTE DISPOSAL METHOD

Contaminated absorbent may be deposited in a landfill in accordance with local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION - NIOSH/MSHA jointly approved air supplied respirator if TLV limits are exceeded. Approved mechanical filter to remove solid airborne particles of overspray during application.

VENTILATION - Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES - Required to prevent prolonged or repeated contact

EYE PROTECTION - Use of safety eyewear is recommended to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT - Impervious clothing & boots are suggested to prevent prolonged or repeated skin contact.

HYGIENIC PRACTICES:

Wash hands before eating, smoking or using bathroom
Do not reuse contaminated clothing.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from heat sparks and open flames. For storage conditions see OSHA 1910.106

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact with skin. Containers should be grounded when pouring.

Avoid free fall of more than 2 - 3 inches when pouring.
