

---

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

**Product ID:** 400.0000623  
Product Name: 623 RUST CONVERTER  
Product Use: Paint product.  
Print date: 03/Jun/2011  
Revision Date: 03/Jun/2011

### Company Identification

The Valspar Corporation - Architectural Coatings Division  
1191 Wheeling Road  
Wheeling, IL 60090

**Manufacturer's Phone:** 1-847-520-8580

**24-Hour Medical Emergency  
Phone:** 1-888-345-5732

## 2. HAZARDS IDENTIFICATION

### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

### Eye Contact:

- Moderate eye irritation

### Skin Contact:

- Causes skin irritation.
- Harmful if absorbed through skin.

### Ingestion:

- Harmful if swallowed.

### Inhalation:

- May cause irritation of respiratory tract.
- Harmful by inhalation.

**Target Organ and Other Health Effects:**

- Spleen damage may occur.
- Liver injury may occur.
- Kidney injury may occur.
- Contains glycol ether which has been shown to cause blood effects damage in laboratory animals.
- Causes headache, drowsiness or other effects to the central nervous system.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

<b>Ingredient Name CAS-No.</b>	<b>Approx. Weight %</b>	<b>Chemical Name</b>
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	2-Butoxyethanol

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

**5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	201
Flash point (Celsius):	94
Lower explosive limit (%):	not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined
Sensitivity to impact:	no
Sensitivity to static discharge:	Sensitivity to static discharge is not expected.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

None known.

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate the area. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment****Eye and face protection:**

Chemical goggles, also wear a face shield if splashing hazard exists.

**Skin protection:**

Appropriate chemical resistant gloves should be worn.

**Other Personal Protection Data:**

To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture.

**Exposure Guidelines****OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	240 mg/m <sup>3</sup> TWA 50 ppm TWA		prevent or reduce skin absorption

**ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	20 ppm TWA			

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	24 mmHg @ 77°F (25°C)
Vapor density (air = 1.0):	4.1
Boiling point:	not determined
Solubility in water:	Complete (soluble in all proportions)
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	9.45
Specific Gravity:	1.134
Evaporation rate (butyl acetate = 1.0):	0.1
Flash point (Fahrenheit):	201
Flash point (Celsius):	94
Lower explosive limit (%):	not determined
Upper explosive limit (%):	not determined
Autoignition temperature:	not determined

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	None known.
Incompatibility:	Avoid water-reactive materials, heat or contact with peroxides or other catalysts.
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide.
<b>Sensitivity to static discharge:</b>	Sensitivity to static discharge is not expected.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5	= 2.21 mg/L Inhalation LC50 Rat 4 h = 220 mg/kg Dermal LD50 Rabbit = 2270 mg/kg Dermal LD50 Rat = 450 ppm Inhalation LC50 Rat 4 h = 470 mg/kg Oral LD50 Rat

**Mutagens/Teratogens/Carcinogens:** None known.

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5			male rat-no evidence; female rat-equivocal evidence; male mice- some evidence; female mice-some evidence

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5			A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: PAINT, NOT REGULATED

### U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

### International Air Transport Association (IATA):

Proper Shipping Name: PAINT, NOT REGULATED

### International Maritime Organization (IMO):

Proper Shipping Name: PAINT, NOT REGULATED

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
ETHYLENE GLYCOL MONOBUTYL ETHER 111-76-2	1 - 5		YES	

### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: no  
Reactivity: no  
Sudden Pressure: no

### U.S. STATE REGULATIONS:

### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

**Pennsylvania Right To Know:**

ETHYLENE GLYCOL MONOBUTYL ETHER

111-76-2

**Additional Non-Hazardous Materials**

WATER

7732-18-5

PROPRIETARY INGREDIENT

Trade Secret

**Rule 66 status of product**

Not photochemically reactive.

**INTERNATIONAL REGULATIONS - Chemical Inventories**

**US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

**Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

**16. OTHER INFORMATION**

**HMIS Codes**

**Health:**

2

**Flammability:**

0

**Reactivity:**

0

**PPE:**

X - See Section 8 for Personal Protective Equipment (PPE).

**Abbreviations:**

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By:

Regulatory Affairs Department

Print date:

03/Jun/2011

Revision Date:

03/Jun/2011