

Product Information

A PRODUCT OF THE VALVOLINE COMPANY A DIVISION OF ASHLAND INC.



VALVOLINE PREMIUM UNIVERSAL TRACTOR FLUID

Valvoline Premium Universal Tractor Fluid is a blend of highly refined base oils and additives designed to lubricate the transmission, differential and final drive gears and serve as a hydraulic medium, power steering fluid, power brake and power take-off fluid in farm tractors. It has excellent extreme pressure and anti-wear properties and provides resistance to rust, corrosion and oxidation. **Valvoline Premium Universal Tractor Fluid** contains an antifoam additive to assist in suppressing foam during use.

Valvoline Premium Universal Tractor Fluid is recommended as a replacement fluid for the following manufacturers specified products:

ABEX/Denison HF-0, HF-2, HF-1	Clark TA12, TA18, HR500, HR600
Allis Chalmers PF-821 XL	Allison C-3, C-4
Caterpillar TO-2	Deutz HTF PF821 XL
IH Hy-Tran, Spec. B-6	Oliver Type 55
Renk Doromat ATF	Sustrand HMS-103
Vickers M-2950-S, I-286-S	Kubota UDT
White Q1722, Q1826	Ford Tractor M2C134B, M2C134C, M2C134D, M2C41B, M2C48B, M2C159B1, M2C159B2
Stieger Hyd. Trans SEMS 17001	Versatile Gear/Hydraulic Transmission Fluid

J.I. Case/David Brown: JIC-143, 144, 145, 185, MS-1204, 1206 (Powergard PTF), 1207, MS-1210 (TCH)
Massey Ferguson: M-1110, M-1127A or B, M-1129-A (Peterman II), M-1135, M-1141 (Permatran III), M-1143
John Deere: Quatrol®, J20A (Hygard 303), J20C, J14B, J14C, J21A, 303

Typical Properties

Gravity (API)	28.0
Gravity (Specific) @ 60° F	0.8872
Flash COC - °F	400
Pour Point °C	-39
Vis @ 40°C (cSt)	65.75
Vis @ 100°C (cSt)	9.5
Vis @ 100°F (SUS)	305
Vis @ 210°F (SUS)	57.6
Viscosity Index	125
Brookfield Vis. @ -20°C, cP	4,870
Brookfield Vis. @ -35°C, cP	48,500
Part Numbers	720 – 5 Gal
	721 – 1 Gal
	725 – 55 Gal

This information only applies to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Code
03-14-03	03-14-05		DJD	