

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.**W. F. Taylor Co., Inc.**

11545 Pacific Avenue
Fontana, CA 92337-8228
951/360-6677
CHEMICAL EMERGENCY HOTLINE 1-800-535-5053

PRODUCT NAME: **ENVIROTEC PRESSURE SENSITIVE TOUCHDOWN**
ITEM NUMBER: 2027-4
ITEM DESCRIPTION: 2027 Envirotec Pressure Sensitive Adh 4-gal
PRODUCT DESCRIPTION: LATEX BASED ADHESIVE
CHEMICAL FAMILY: ACRYLIC LATEX, RESIN BLEND
REVISION DATE: 10/30/07

HMIS HAZARD RATING

LEAST: 0 HEALTH: 1
SLIGHT: 1 FLAMMABLE: 0
MODERATE: 2 REACTIVITY: 0
HIGH: 3
EXTREME: 4

PREPARED BY: DARWIN C. REGIS
PREEMPTS PREVIOUS MSDS SHEETS

SECTION II HAZARDOUS INGREDIENTS

<u>COMPONENT/CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>% WT</u>	<u>NOTES</u>
NO HAZARDOUS INGREDIENTS PER CURRENT OSHA REGULATIONS				

SECTION III PHYSICAL DATA

BOILING POINT: 212 DEGREES F
LBS / GAL: 8.5 - 9.0
EVAPORATION RATE: SAME AS WATER
VAPOR DENSITY: SAME AS WATER.
PERCENT VOLATILE: 47 -50 (BY WEIGHT)
COLOR: OFF WHITE
ODOR: NIL
GRAMS V.O.C. PER LITER OF MATERIAL: NEGLIGIBLE

SECTION IV FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, PENSKEY-MARTIN C.C.: NA
AUTO IGNITION TEMPERATURE, DEGREES F: NA
FLAMMABLE LIMITS IN AIR (% BY VOLUME): LEL: NA UEL: NA
EXTINGUISHING MEDIA:

(X) WATER SPRAY (X) CARBON DIOXIDE () OTHER
(X) FOAM (X) DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF CONTAINED BREATHING APPARATUS.
UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN

SECTION V HEALTH HAZARD IDENTIFICATION

SYMPTOMS OF OVER EXPOSURE:
INHALATION: MAY CAUSE SLIGHT IRRITATION TO THE UPPER RESPIRATORY TRACT.
EYES: VAPOR MAY CAUSE IRRITATION.
SKIN: MAY CAUSE SLIGHT SKIN IRRITATION.
INGESTION: NOT A LIKELY ROUTE OF ENTRY UNDER PROPER HANDLING CONDITIONS. MAY CAUSE VOMITING. SYMPTOMS MAY BE SAME AS INHALATION.

PRODUCT NAME: **ENVIROTEC PRESSURE SENSITIVE TOUCHDOWN**
ITEM NUMBER: 2027-4
ITEM DESCRIPTION: 2027 Envirotec Pressure Sensitive Adh 4-gal
REVISION DATE: 10/30/07

HEALTH EFFECTS OR RISK FROM EXPOSURE:

ACUTE: INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTACT WITH EYES AND SKIN MAY RESULT TO IRRITATION. INGESTION MAY RESULT TO GASTRIC DISTURBANCES.

CHRONIC: NOT KNOWN

SECTION VI FIRST AID PROCEDURES

FIRST AID PROCEDURES:

EYES CONTACT: WASH WITH WATER AT LEAST 15 MINUTES. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

SKIN CONTACT: REMOVE FROM SKIN AND WASH WITH SOAP AND WATER. IF IRRITATIONS PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. ADMINISTER OXYGEN, IF NECESSARY. SEEK MEDICAL ATTENTION.

INGESTION: IF SWALLOWED, CALL PHYSICIAN.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

SECTION VII HANDLING AND STORAGE

PRECAUTION FOR HANDLING AND STORING: DO NOT PUNCTURE.

KEEP OUT OF THE REACH OF CHILDREN.

PROTECT FROM FREEZING

CAUTION: DO NOT TAKE INTERNALLY. IF SWALLOWED, DO NOT INDUCE VOMITING, CALL PHYSICIAN IMMEDIATELY.

SECTION VIII SPECIAL PROTECTION INFORMATION

VENTILATION AND ENGINEERING CONTROLS: USE LOCAL EXHAUST. DO NOT USE CLOSED AIR-CIRCULATING SYSTEM. OPEN WINDOWS AND DOORS IF NECESSARY.

RESPIRATORY PROTECTION: NIOSH RESPIRATOR IF NEEDED.

CLOTHING: CHEMICAL RESISTANT GLOVES, APRON, COVERALLS, AND BOOTS AS NECESSARY TO PREVENT CONTACT.

EYE PROTECTION: CHEMICAL GOGGLES OR FACE SHIELD

OTHER CLOTHING AND EQUIPMENT: IF CLOTHING BECOMES CONTAMINATED, REMOVE AND CLEAN BEFORE REWEARING.

WORK PRACTICES, HYGIENIC PRACTICES: FOLLOW LABEL INSTRUCTIONS.

PROTECTIVE MEASURES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: USE GOGGLES AND GLOVES WHEN CLEANING ADHESIVE FROM EQUIPMENT. MAINTAIN PROPER VENTILATION.

SECTION IX SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED

KEEP OUT OF SEWER SYSTEMS TO PREVENT BLOCKAGE DUE TO POLYMER DEPOSITS. USE ABSORBENT MATERIAL TO COLLECT AND/OR SCRAPE UP EXCESS AND PLACE INTO CLOSED DOT APPROVED CONTAINERS FOR DISPOSAL.

SECTION X STABILITY AND REACTIVITY DATA

STABILITY: STABLE

FREEZE THAW STABILITY: UP TO 5 CYCLES AT 10 DEGREES F

CONDITIONS TO AVOID: KEEP AWAY FROM EXTREME TEMPERATURE CONDITIONS.

INCOMPATIBILITY-MATERIALS TO AVOID: OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION PRODUCTS (INCLUDING COMBUSTION PRODUCTS): OXIDES OF CARBON, WATER AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

PRODUCT NAME: **ENVIROTEC PRESSURE SENSITIVE TOUCHDOWN**
ITEM NUMBER: 2027-4
ITEM DESCRIPTION: 2027 Envirotec Pressure Sensitive Adh 4-gal
REVISION DATE: 10/30/07

SECTION XI TOXICOLOGICAL PROPERTIES

NOT AVAILABLE

SECTION XII ECOLOGICAL INFORMATION

NOT AVAILABLE

SECTION XIII DISPOSAL CONSIDERATION

WASTE DISPOSAL: ABIDE BY ALL STATE, FEDERAL AND LOCAL REGULATIONS

SECTION XIV: TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: NOT APPLICABLE
PROPER HAZARD CLASS: NOT HAZARDOUS
HAZARD CODE: NOT HAZARDOUS

SECTION XV REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD(29CFR 1910.1200)HAZARD CLASS(ES): NONE
SARA TITLE III SECTION 312 HAZARD CLASS: NONE
EPA SARA TITLE III SECTION 313: NONE

CALIFORNIA PROPOSITION 65: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR REPRODUCTIVE HARM.

SECTION XVI OTHER INFORMATION

W.F. TAYLOR BELIEVES THE DATA SET FORTH HEREIN ARE ACCURATE AS OF THE DATE HEREOF. TAYLOR MAKES NO WARRANTY WITH RESPECT THERETO AND EXPRESSLY DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. SUCH DATA ARE OFFERED SOLELY FOR YOUR CONSIDERATION, INVESTIGATION AND VERIFICATION.
