



HAZARD RATING	
HEALTH	: 2
FIRE	: 4
REACTIVITY	: 0
PERSONAL PROTECTION	: A

Well-Worth Products, Inc. Material Safety Data Sheet

SECTION I PRODUCT IDENTIFICATION AND USE

PRODUCT NAME: Black Beauty 16 oz # 2002

MANUFACTURER / SUPPLIER: Well-Worth Products, Inc.

ADDRESS: 180 Dutton St., Buffalo, NY 14211

PHONE: 716-597-0214, 800-890-7935

EMERGENCY PHONE: 800-890-7935

PRODUCT USE: Rubber Treatment

SECTION II HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS:	WT%:	CAS. NO:	OSHA PEL:	AGGIH TLV:	STEL:
* Isopropanol	1-20%	67-63-0	400ppm	400ppm	500
N-Butane	1-10%	106-97-8	800ppm	800ppm	ASPHX
Propane	1-10%	74-98-8	1000ppm	1000ppm	ASPHX
Isobutane	1-10%	76-28-6	800ppm	800ppm	ASPHX

SECTION III PHYSICAL DATA

ODOR & APPEARANCE: Characteristic solvent odor

BOILING POINT: -40-180F	MELTING POINT: -Liquid: NA	VAPOR PRESSURE: @70F: 65-75	VAPOR DENSITY: (Air=1) yes Heavier than air
SOLUBILITY IN WATER: Negligible	%VOLATILE: 50%	EVAPORATION RATE: >1.0 (Water=1)	SPECIFIC GRAVITY: 0.76

SECTION IV FIRE AND EXPLOSION DATA

FLASH POINT PROPELLANT / FLASH POINT PRODUCT: -40 F / 53 F (TCC)	FLAMMABLE LIMITS: LEL; N/A 1.8	UEL; N/A 8.4
EXTINGUISHING MEDIA: Use water fog, dry chemical or carbon dioxide		
SENSITIVITY TO STATIC DISCHARGE: n/d		
SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear NIOSH approved positive pressure self-contained breathing apparatus. Aerosol cans may rupture when heated.		
UNUSUAL FIRE AND EXPLOSION HAZARDS: Heated cans may burst. Keep away from heat sparks or open flame		

SECTION V REACTIVITY DATA

STABILITY: Stable: Yes	CAN HAZARDOUS POLYMERIZATION OCCUR: Will not occur.
INCOMPATIBLE MATERIALS: Strong acids and bases, oxidizers	HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, products of incomplete
CONDITIONS TO AVOID: None	

SECTION VI TOXICOLOGICAL PROPERTIES

POSSIBLE ROUTES OF ENTRY: <input checked="" type="checkbox"/> SKIN CONTACT <input type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE CONTACT <input checked="" type="checkbox"/> INHALATION <input checked="" type="checkbox"/> INGESTION
EFFECTS OF ACUTE EXPOSURE: May cause dizziness or narcosis in high vapor concentrations. Will cause defatting of skin. Effects are reversible.
EFFECTS OF CHRONIC OVEREXPOSURE TO PRODUCT: Long term exposure (years) to vapor may cause lung, liver or kidney damage. The solvents listed have been reported to affect the central nervous system:
CARCINOGENICITY: not presently on any list.

SIGNS AND SYMPTOMS OF EXPOSURE:

EYES: Blurred vision	DERMAL: Redness	INHALATION: Difficulty in breathing	INGESTION: Vomiting-alcohol consumed before or after may increase adverse effects.
----------------------	-----------------	-------------------------------------	--

SECTION VII PREVENTIVE MEASURES	
GLOVES: None required if spraying	
RESPIRATOR: Local Exhaust. If TLV limits are exceeded use a self contained breathing apparatus.	
EYES: Safety glasses or goggles	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Long sleeves and long pants or coveralls.	
WORK / HYGENIC PRACTICES: Do not smoke while using. Wash hands after use. Concentrated vapors of this product are heavier than air and will collect in low areas, pits, storage tanks and other confined spaces. Do not enter these areas. Avoid breathing of vapors. Keep out of reach of children. Notice: Reports have associated repeated and prolonged occupational damage. Intentional misuse by concentrating and inhaling this product may be harmful or fatal. If you have a medical condition consult with a physician prior to using this product.	
LEAK / SPILL PROCEDURES: Use absorbent sweeping compound to soak up material. Pour into container. Dispose as hazardous waste.	
WASTE DISPOSAL: Dispose of waste in accordance with applicable Federal, State and local requirements.	
STORAGE REQUIREMENT: Keep away from heat, sparks or open flame. Store at temperatures below 120° F.	
SECTION VIII FIRST AID MEASURES	
INHALATION: Remove to fresh air. Give oxygen. Contact physician.	
INGESTION: Do not induce vomiting-gastric lavage. Contact physician.	
EYE CONTACT: wash eyes with fresh water. If irritation continues, contact physician.	
SKIN CONTACT: wash skin with fresh water. If irritation continues, contact physician.	
PREPARATION DATA	
PREPARATION DATE: 5-02	PREPARED BY: QC SUPERVISOR
OTHER INFORMATION	
<ul style="list-style-type: none"> Starred items are subject to the reporting requirements of Sara 313 and 40 CFR 372. If any of the components in Section II are preceded by a star (*) you must notify each person to whom this product is sold. State of California Proposition 65. Not presently on any list. New Jersey Right to Know: hexane, propane, isobutane, n.Butane, Grease VOC = 3.2 pounds/gal 365 grams/liter	
TRANSPORTATION INFORMATION	
DOT Shipping- Consumer Commodity Orm-D	
DO NOT SHIP BY AIR	

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

© WELLWORTH PRODUCTS, 2001